

Issuing Date 06-Jan-2017

Revision Date 06-Jan-2017

SAFETY DATA SHEET

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier	
Product Name	LITHIUM CSC & PMX CELLS AND BATTERIES
Other means of identificatio	<u>n</u>
UN-Number	UN3090
Synonyms	Hermetically-Sealed Lithium Sulfuryl Chloride Cells and Batteries
<u>Recommended use of the ch</u> Recommended Use Uses advised against	hemical and restrictions on use No information available Do not short circuit or expose to temperatures higher than the maximum temperature rating
	specified by the manufacturer. Do not recharge, over charge or crush any cell or pack. Ensure cells and batteries are safely handled and stored. Review Section 7 completely

Supplier's details

Supplier Address	Manufacturer Address
Integer Holdings Corp.	Electrochem Solutions
2595 Dallas Pkwy #310	670 Paramount Drive
Frisco, TX 75034	Raynham, MA 02767
TEL: 214-618-5248	TEL: 781-830-5800

Emergency telephone number

Emergency	Telephone
Number	

1-800-424-9300 (Chemtrec Account 24706)

2. HAZARDS IDENTIFICATION

Classification


This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an SDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute Inhalation Toxicity - Gas	Category 1
Acute Inhalation Toxicity - Vapors	Category 1
Skin Corrosion/Irritation	Category 1 Subcategory 1B
Serious Eye Damage/Eye Irritation	Category 1
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3

GHS Label elements, including precautionary statements

UN3090 discussed in the following pages is appropriately packaged in equipment and therefore being shipped as UN3091

Emergency Overview



Precautionary Statements

Prevention

- Do not breathe dust/fume/gas/mist/vapors/spray.
- Use only outdoors or in a well-ventilated area.
- Wear respiratory protection
- Wash face, hands and any exposed skin thoroughly after handling.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- · Specific treatment is urgent (see supplemental instructions on the administration of antidotes on this label)
- Immediately call a POISON CENTER or doctor/physician.
- Specific treatment (see supplemental instructions on the administration of antidotes on this label)

Eyes

• IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

• Immediately call a POISON CENTER or doctor/physician.

Skin

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Wash contaminated clothing before reuse.

Inhalation

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Immediately call a POISON CENTER or doctor/physician.
- Call a POISON CENTER or doctor/physician if you feel unwell.

Ingestion

• IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

Storage

- Store in a well-ventilated place. Keep container tightly closed.
- Store locked up.

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Cells and batteries may be explosive if exposed to higher temperatures. Do not expose cells or batteries to temperatures above the maximum rated temperature as specified by the manufacturer.

Other information

7% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

Hermetically-Sealed Lithium Sulfuryl Chloride Cells and Batteries

Chemical Name	CAS-No	Weight %	Trade secret
Sulfuryl chloride	7791-25-5	25-39	*
Lithium	7439-93-2	1.5-5	*
*The event percentage (concentration) of composition has been withheld as a trade accurat			

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General AdviceFirst aid is upon rupture of sealed battery:Eye ContactIF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
present and easy to do. Continue rinsing. Call a physician or Poison Control Center
immediately.Skin ContactIF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin
with water/shower. Consult a physician.InhalationIF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position
comfortable for breathing. Call a physician or Poison Control Center immediately.IngestionIF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse
mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Itching. Burning. Difficulty in breathing. Coughing and/ or wheezing. Serious eye irritation or damage.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Use of water spray when fighting a lithium fire may be inefficient. However, copious amounts of water may be used to cool a battery fire and extinguish any surrounding combustible fires.

Specific Hazards Arising from the Chemical

The electrolyte will release toxic sulfur dioxide gas.

Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment. Wash thoroughly after handling. Refer to Section 8 for personal protective equipment.
Environmental Precautions	
Environmental Precautions	See Section 12 for additional Ecological Information.
Methods and materials for containr	nent and cleaning up
Methods for Containment	Prevent further leakage or spillage if safe to do so and properly trained.
Methods for Cleaning Up	During a release, ensure the Personal Protection listed in Section 8 is worn. Neutralize any electrolyte contaminated surfaces with baking soda, soda line or sodium bicarbonate. Transfer damaged battery and any clean up materials to a sealed container a neutralizing material as stated above. Ensure the container is properly labeled.

7. HANDLING AND STORAGE

Precautions for safe handling	
Handling	Do not crush, pierce, short circuit (+) and (-) battery terminals with conductive (metal) goods. Do not directly heat or solder. Do not throw into fire. Do not mix batteries of different types and brands. Do not mix new and used batteries. Keep batteries in non-conductive (plastic) trays. Cells or batteries that have been dropped or experience mechanical shock should be isolated and monitored for approximately 5 days to identify a possible internal short circuit and resulting fire. In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. Avoid contact with skin, eyes and clothing. Do not breathe vapors/dust. Wear personal protective equipment.
Conditions for safe storage, includ	ling any incompatibilities
Storage	Store at room temperature. Do not store in high humidity environments. Do not store near combustible or flammable materials. Never stack heavy objects on top of battery boxes. Keep batteries in original packaging until use and do not expose them to unnecessary or excessive handling.
Incompatible Products	Under normal use, batteries are not incompatible. The electrolyte is incompatible with: Strong acids. Strong bases. Strong oxidizing agents.
8. EX	POSURE CONTROLS / PERSONAL PROTECTION
Control parameters	
Exposure Guidelines	This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.
Appropriate engineering controls	
Engineering Measures	Showers Eyewash stations Ventilation systems
Individual protection measures, su	ich as personal protective equipment
Eye/Face Protection	None required for normal handling of the finished product. If necessary to handle damaged product where exposure to the electrolyte is a possibility, chemical splash goggles and a face shield are recommended.

Skin and Body Protection	None required for normal handling of the finished product. If necessary to handle damaged product where exposure to the electrolyte is a possibility, chemically resistant gloves and apron are recommended.
Respiratory Protection	None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Odor	Solid. None.	Appearance Odor Threshold	No information available. No information available.
Cuci	None.		No momation available.
Property	Values		s/ - Method
pH	Not applicable unle		own
	exposure to an ele		
Melting Point/Range	Not applicable unle		Chloride: - 54 °C
Boiling Point/Boiling Range	exposure to an ele		Chlorida: 67 60.4 °C
Bolling PolityBolling Range	Not applicable unle exposure to an ele		Chloride: 67 - 69.4 °C
Flash Point	Not applicable unle		מאר
	exposure to an ele		5.001
Evaporation rate	Not applicable unle		own
•	exposure to an ele		
Flammability (solid, gas)	Not applicable unle		own
	exposure to an ele	ctrolyte.	
Flammability Limits in Air			
upper flammability limit	Not applicable unle		
	exposure to an ele		
lower flammability limit	Not applicable unle exposure to an ele		
Vapor Pressure	Not applicable unle		Chloride: 148 hPa @ 20 °C
Vapor riessure	exposure to an ele		Chloride: 993 hPa @ 68 °C
Vapor Density	Not applicable unle		own
	exposure to an ele		
Specific Gravity	Not applicable unle		Chloride: 1.66
	exposure to an ele		
Water Solubility	Not applicable unle		own
	exposure to an ele		
Solubility in other solvents	Not applicable unle		own
Partition coefficient: n-octand	exposure to an ele		awa
rantition coemcient. n-octain	exposure to an ele		5001
Autoignition Temperature	Not applicable unle		own
5	exposure to an ele		
Decomposition Temperature	Not applicable unle		own
	exposure to an ele		
Viscosity	Not applicable unle		own
	exposure to an ele	ctrolyte.	
Flammable Properties	Not flammable		
Explosive Properties		ess there is exposure to an ele	
Oxidizing Properties	Not applicable unle	ess there is exposure to an ele	ectrolyte.
VOC Content (%)	Not applicable unle	ess there is exposure to an ele	ectrolyte.

10. STABILITY AND REACTIVITY

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal use. In the event of a leak or rupture: electrolyte and lithium will react with water.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Ignitions sources - heat, sparks and open flames.

Incompatible materials

Under normal use, batteries are not incompatible. The electrolyte is incompatible with: Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Lithium oxides, Sulfur dioxide, Hydrogen chloride, Chlorine.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Exposure is not expected for product under normal conditions of use. In the event of an exposure to electrolyte the following toxicological information is provided:
Inhalation	Fatal if inhaled.
Eye Contact	Corrosive to the eyes and may cause severe damage including blindness.
Skin Contact	Corrosive to rabbit skin (4hr).
Ingestion	May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Sulfuryl chloride	-	-	= 159 ppm (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Burning. Eye and skin redness, tearing, hives, blurry vision. May cause blindness.			
Delayed and immediate effects and also chronic effects from short and long term exposure				
Sensitization	No information available.			
Mutagenic Effects	No information available.			
Carcinogenicity	Contains no ingredients above reportable quantities listed as a carcinogen.			
Reproductive Toxicity	No information available.			
STOT - single exposure	Contains a component known to cause systemic target organ toxicity from acute exposure.			
STOT - repeated exposure	No information available.			
Target Organ Effects	Eyes. Skin. Respiratory system. Gastrointestinal tract (GI). Kidney. Liver.			
Aspiration Hazard	No information available.			

<u>Numerical measures of toxicity</u> - Unknown acute toxicity	Product				
	ed based on chapter 3.1 of the GHS document:				
Inhalation					
gas	44				
Vapor	0.4 mg/L; Acute toxicity estimate				
	12. ECOLOGICAL INFORMATION				
Ecotoxicity					
Avoid any release to waterways, group	undwater, or any environmental media. Harmful effects due to pH shift are expected.				
Persistence and Degradability	No information available.				
Bioaccumulation	No information available.				
Other Adverse Effects No information available.					
	13. DISPOSAL CONSIDERATIONS				
Waste Disposal Methods	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR				
	261).				
Contaminated Packaging	Do not re-use empty containers.				
	14. TRANSPORT INFORMATION				
Note:	Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code". For Specific transport information for all variations of BCX cells, please review the Product Data Sheet. This can be sent upon request. Please contact				
DOT	the manufacturer.				
<u>DOT</u> UN-Number	UN3090				
Proper shipping name					
Hazard Class	Lithium metal battery				
	9 UNI2000 Lithium metel hetteries 0				
Description Emergency Response Guide Number	UN3090, Lithium metal batteries, 9 138				
	Forbidden by Passenger Air				
UN-Number	UN3090				
Proper Shipping Name	Lithium metal batteries				
Hazard Class	9				
ERG Code	9FZ				
Description	UN3090, Lithium metal batteries, 9				
IMDG/IMO					
UN-Number	UN3090				
Proper Shipping Name	Lithium metal batteries				
Hazard Class	9				
EmS No.	F-A, S-I				
Description	UN3090, Lithium metal batteries, 9				
	15. REGULATORY INFORMATION				
International Inventories	All components of this product are either listed or are exempt on the TSCA inventory.				

All components of this product are either listed or are exempt on the TSCA inventory.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

<u>CERCLA</u>

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Sulfuryl chloride	Х	Х	Х		Х
Lithium	Х	Х	Х		Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION							
NFPA	Health Hazard 0	Flammability 0	Instability 0	Physical and Chemical Hazards -			
HMIS	Health Hazard 0	Flammability 0	Physical Hazard 0	Personal Protection X			
Prepared By	23 British	Stewardship American Blvd. NY 12110 2-6501					
Issuing Date Revision Date Revision Note	06-Jan-2 06-Jan-2 Initial Re	017					

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet