HAWAII OCEAN TIME-SERIES HOT- 158 General Cruise Plan

VESSEL: R/V Kaimikai O Kanaloa, University of Hawaii

MASTER OF THE VESSEL: Ross Barnes

CHIEF SCIENTIST: Dan Sadler, University of Hawaii

STAG Deck Technician: Dave Gravatt STAG Electronics Technician: Steve Poulos

Load: Apr. 16, 2004 0900 HST Depart: Apr. 19, 2004 0900 HST Return: Apr. 23, 2004 0800 HST

1.0. SCIENTIFIC OBJECTIVES

The objective of HOT 158 is to maintain collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) Station ALOHA, our near shore station Kahe Point and Kaena Pt. station. Kahe Point (21°20.6'N, 158°16.4'W) is occuppied enroute to Station ALOHA to test equipment and collect nearshore data. Station ALOHA is defined as a circle with a 6 nautical mile radius centered at 22°045'N, 158°W. Kaena Point station (21°50.8'N, 158°21.8'W), will be occupied on the return transit to Honolulu.

1.1 SCIENTIFIC OPERATIONS

<u>Station</u>	<u>Activities</u>
----------------	-------------------

Kahe (sta. 1) Weight Cast, PRR cast, CTD cast (1000 m)

ALOHA (sta. 2) Sediment traps, net tows, CTD op's, PRR casts, primary

productivity measurements, AC9, misc. experiments

Kaena Pt. (sta. 6) CTD op's (2500 m)

Underway/continuous ADCP, thermosalinograph, fluorometry, meteorology

2.0. SCIENCE PERSONNEL

UH/BGC&E	Research Specialist
UH/BGC&E	Research Associate
UH/BGC&E	Research Specialist
UH/BG&CE	Graduate Student
UH/PO	Research Associate
UH/BGC&E	Computer Specialist
UH/BGC&E	Graduate Student
UH/STAG	Deck Technician
UH/PO	Graduate Student
UH/HIMB	Scientist
UH/PO	Research Associate
UH/BGC&E	Volunteer
	UH/BGC&E UH/BGC&E UH/BG&CE UH/PO UH/BGC&E UH/BGC&E UH/STAG UH/PO UH/HIMB

Poulos, Steve UH/STAG Electronics Technician Sadler, Dan (Chief Scientist) UH/BGC&E Research Associate Simmons, Melinda SIO/BGC&E Graduate Student Valenciano, Mark UH/PO Electronics Technician Watkins, Blake UH/BGC&E Marine Engineer

3.0. SUMMARY SCHEDULE

16 Apr. Ship loading starting at 0900 hrs

19 Apr. Depart from Snug harbor at 0900 hrs. Science personnel on-board by 0830.

19 Apr. Station 1 Kahe Pt. operations20-22 Apr. Station ALOHA operations

22 Apr. Sediment trap array retrieval, Station 8 CTD ops.23 Apr. Return to Snug harbor. ETA 0800 hrs, full offload

4.0. OPERATIONAL PLANS

4.1. Kahe Point Station (21°20.6'N, 158°16.4'W)

Operations at Kahe station include an initial weight cast to 1000 m, followed by a hand-lowered light cast (PRR-600); and CTD cast to 1000 m. After all operations have been completed the ship shall proceed to Sta. ALOHA.

4.2. Station ALOHA (22°45'N, 158°W with 6 nmile radius)

Upon arrival at Station ALOHA a net tow will be conducted, followed by deployment of the floating sediment traps. After the trap deployment CTD operations will begin. As usual the first cast will be to near-bottom, followed by the 36 hr, 3 hr interval "burst" sampling. Interspersed in this time frame are PRR and optics casts, primary production cast/array deployment/retrieval, additional plankton net tows, and misc. experiments.

4.2.1. Plankton net tows

A series of plankton net tows will be conducted off the stern. We request the use of the ship's tow winch and A-frame for these operations. Hour periods are scheduled at around noon and midnight (see day-hour schedule) in excess of the six required in the event of equipment problems and/or rough sea conditions.

4.2.2. Floating Sediment Trap deployment

The floating sediment traps will be deployed from the center of Station ALOHA. The array will be deployed from the stern using the knuckle crane and the JGOFS DSE winch. Power requirement for the winch is 440 VAC, three phase at 10 amps. After deployment we would like to return to the center of Station ALOHA and commence with CTD operations.

The array will drift for approximately 55 hours before recovery. The array is equipped with 2 ARGOS satellite transmitters (platform # 01325 & 01833), 2 strobe lights, and 2 radio transmitters (channel 74, 156.725 MHz). Daily positions of the array shall be transmitted by email directly to the ship. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array.

4.2.3. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Seabird CTD attached to a 24-place rosette with 12 liter sampling bottles. The CTD winch and hydroboom will be used for this operation. Water samples for biogeochemical measurements will also be collected on each cast. The first cast shall be made to the near bottom (approximately 4800 m). Following this cast, a series of casts shall be made continuously every 3

hours for a 36-hour period, after which a second full-depth cast will be conducted. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, repositioning to the center of the Station before each cast whenever possible. A 100 m cast will be conducted immediately prior to final departure from Station ALOHA.

4.2.4. Primary production experiment

Samples for the primary productivity experiment will be collected from the rosette (cast 8). Just before dawn, a second free drifting array with incubation samples will be deployed from the stern. We request the use of the knuckle crane for this operation and will also use the JGOFS DSE winch. The array is equipped with a strobe light and a radio transmitter (channel 72, 156.625 MHz). The ship shall keep within sight of the array while performing CTD operations for the approximately 12 hour duration the array will be in the water. The array will be recovered around sunset. CTD operations shall continue after the recovery.

4.2.5. Profiling Reflectance Radiometer (PRR)

Around noon on each day a profiling reflectance radiometer will be deployed from the main deck using the starboard crane. This instrument is hand-lowered and retrieved with assistance from the capstan or our DSE winch.

4.2.6. AC9/FRRF

The Wet Labs AC9 is an optical instrument that measures water column spectral absorption and attenuation at nine wavelengths. The AC9 package also includes a Sea-Bird Seacat with temperature, conductivity, pressure and fluorometer sensors. The package will be deployed to a target depth of 150 m from the starboard side. We request the use of the tow winch for this deployment. The slow sampling rate of these instruments requires a winch speed of 10 m/min.

4.3. Floating Arrays

After operations at Sta. ALOHA have been completed we shall proceed for the recovery of the sediment trap array. We will retrieve the sediment trap array at daybreak. The starboard crane and the JGOFS DSE winch will be needed for this operation.

4.4 Kaena Point (Station 6)

The final station will be station 6, Kaena Point ($21^{0}50.8$ 'N, $158^{0}21.8$ 'W), on the return transit. Here a near-bottom (\sim 2500 m) CTD cast will be conducted before returning to Snug Harbor.

5.0 EQUIPMENT

5.1 The HOT science party shall bring the following:

- 1. Sea-Bird CTD system, all sensors, deck boxes and computer CTD acquisition systems.
- 2. 24-place rosette with 12-l water sampling bottles, all spare parts
- Two laboratory vans with assorted laboratory equipment for radioisotope and sample processing work.
- 4. All required sampling bottles
- 5. Type I and Type II water and all required chemicals and isotopes
- 6. Storage van with assorted equipment.
- 7. Large vacuum waste container
- 8. Liquid nitrogen dewars
- 9. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights, spar buoy

- 10. Drifting primary productivity array with strobe light, radio transmitter, floats, weights, polyproline, spar buoy etc.
- 11. Plankton nets
- 12. Dissolved oxygen measurement system
- 13. Desktop and laptop personal computers
- 14. PRR, AC-9 & other optical measuring instruments
- 15. Pertinent MSDS
- 16. DSE winch
- 17. Incubator

5.2 We will need from the ship the following:

- 1. A-Frame
- 2. A-frame block assembly
- 3. Knuckle crane
- 4. CTD winch
- 5. Electric power for winch (440 VAC three phase at 10 amps) and vans (208 VAC single phase at 30 amps for labvan, 110 VAC 10 amps for equipment van)
- 6. Radio direction finder
- 7. Empty freezer and refrigerator in wet lab
- 8. Space on the main deck for one labvan and space on the 03 deck for one equipment van
- 9. Hand-held VHF transceivers
- 10. Precision depth recorder
- 11. Shackles, hooks and lines
- 12. Shipboard Acoustic Doppler Current Profiler
- 13. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer
- 14. Grappling hooks and line
- 15. Running fresh water and seawater hoses
- 16. Electronic mail system
- 17. GPS system
- 18. Navlink2 PC or equivalent
- 19. Uncontaminated seawater supply
- 20. Tow winch for nets and AC9-FRRf deployments

SHIP <u>R/V KOK</u> <u>HOT 158</u> DATE <u>19-23 Apr, 2004</u>

SHIP <u>R</u>	<u> </u>	<u>HOT 1</u>	158	DATE <u>19-23 A</u>	<u>pr, 2004</u>
TIME	Mon. 4/19	Tue. 4/20	Wed. 1/21	Thu. 4/22	Fri. 4/23
0000		Arrive ALOHA Net tow			
0100		Deploy sed. traps	Net tow		
0200		S2C1 PO-1	S2C8 PP		
0300				AC9-FRRf	
0400				Transit sed traps	
0500			S2C9 Open		
0600			Deploy PP array Log PRR Light		
0700				Recover sed traps	
0800	On Board	S2C2 PO-2 (start 36 hrs)	S2C10 PSi	Transit ALOHA	Arrive Snug Full Offload
0900	Depart Snug Log Licor light				
1000		Net tow	Net tow		
1100		S2C3 MIT	S2C11 Open	PRR	
1200	Arrive Kahe Weight cast		PRR AC9-FRRf	AC9-FRRf	
1300	PRR	Net tow	Net tow	AC9-FRRf	
1400	S1C1 (Kahe)	S2C4 P.PO4	S2C12 ATP	S2C16 Particles	
1500	Transit ALOHA			Transit St. 6	
1600					
1700		S2C5 PC/PN	S2C13 Open		
1800					
1900			Recover PP array End PRR Light		
2000		S2C6 PE	S2C14 HPLC (end 36 hrs)		
2100				S6C1 (Kaena)	
2200		Net tow	Net tow		
2300		S2C7 JGOFS-2	S2C15 PO-3	Transit Snug	

HOT-158 Watch Schedule

<u>0300-1500</u>

- D. Fitzgerald Watch Leader
- M. Valenciano
- L. Fujieki
- D. Sadler (Chief Scientist)
- E. Dafner

1500-0300

- K. Björkman
- M. Iriondo
- X. Murard
- T. Clemente
- B. Watkins Watch Leader

At-large

- M. Simmons
- M. Rappe
- T. Peery
- M. Grabowski
- B. Deschenes

19-23 Apr., 2004 Ship: R/V KOK

HOT 158 CTD CASTS

	Cast	Samples	#Bottles			
Kahe Pt.						
s1c1	1000 m	O ₂ , Temp, DIC/Alk, Nuts, Chl a, LLN, LLPO ₄ , DOC, FCM, Salts,	24			
Station	ALOHA					
s2c1	4800 m (PO-1)	O ₂ , Temp, DOC, DIC/Alk, Nuts, Salts	24			
s2c2	1000 m (PO-2)	O ₂ , Temp, Nuts, DIC/Alk, Quay, DOC, Salts	24			
s2c3	1000 m	MIT, Salts	14			
s2c4	1000 m	PPO4, Salt	14			
s2c5	1000 m	PC/PN, Salts	14			
s2c6	1000 m	PE, Salts	14			
s2c7	1000 m (JGOFS-2)	O ₂ , Temp, DIC/Alk, Nuts, LLN, LLP, DOC, Keeling, Quay, Salts	19			
s2c8	1000 m	Primary Productivity, Chl a, FCM, Salts	22			
s2c9	1000 m	Salts	4			
s2c10	1000 m	PSi, Salts	10			
s2c11	1000 m	Salts	4			
s2c12	1000 m	ATP, Salts	11			
s2c13	1000 m	Salts	4			
s2c14	1000 m	HPLC, Chl a, Salts	14			
s2c15	4800 m (PO-3)	O ₂ , Temp, Salts, WOCE	9			
s2c16	100 m	Particles	4			
Kaena Point						
s6c1	2500 m	Open, Chl a Salts	13			