Hawaii Ocean Time-series HOT-197 General Cruise Plan

Vessel: R/V Kilo Moana, University of Hawaii Master of the Vessel: Captain Richard Meyer

Chief Scientist: Fernando Santiago-Mandujano, University of Hawaii

OTG Marine Technicians: Kuhio Vellalos and Tobin Chen

Loading: November 29, 2007 @ 1200. Departure: November 30, 2007 @ 0900 Arrival: December 4, 2007 @ 0800

1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Four stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at 21° 20.6'N, 158° 16.4'W and will be occupied on the first day of the cruise for about 2 hours.
- 2) Station 2, referred to as Station ALOHA is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied during the 2nd, 3rd, and 4th days of the cruise.
- 3) Station 52, is the site of the WHOTS Mooring, located at 22° 40.208'N, 157° 57.001'W will be occupied on the 4th day of the cruise for about one hour.
- 4) Station 6, referred to as Station Kaena, is located off Kaena Point at 21° 50.8'N, 158° 21.8'W will be occupied on the 4th day of the cruise for about 2 hours.

1.1 **SCIENTIFIC OPERATIONS**

Station	Activities
Kahe (sta. 1) ALOHA (sta. 2)	Weight Cast, PRR cast, CTD cast (1000 m) Sediment traps, gas array, net tows, CTD operations, primary productivity measurements, AC9/FRRf, misc. experiments.
WHOTS mooring station (Sta. 52)	One CTD cast (200 m).
Kaena (sta. 6) Underway/continuous	CTD cast (2400 m) ADCP, thermosalinograph, fluorometry, meteorology

2.0. SCIENCE PERSONNEL

Participant	Title	Affiliation/HOT Group	
Karin Björkman	Research Specialist	UH/BEACH	

Tara Clemente	Research Associate	UH/BEACH
Susan Curless	Research Associate	UH/BEACH
Lance Fujieki	Computer Specialist	UH/BEACH
Adriana Harlan	Technician	UH/BEACH
Binglin Li	Graduate Student	UH/BEACH
Donn Viviani	Graduate Student	UH/BEACH
Brett Updyke	Technician	UH/BEACH
Blake Watkins	Marine Engineer	UH/BEACH
Sam Wilson	Scientist	UH/CMORE
Paul Lethaby	Research Associate	UH/PO
Fernando Santiago-Mandujano	Chief Scientist – Res. Assoc.	UH/PO
Christin Shacat	Research Associate	UH/PO
Justin Smith	Undergraduate Student	UH/PO
Jefrey Snyder	Marine Technician	UH/PO
Misty Miller	Technician	UH/Rappe
Naomi Wagoner	Technician	UH/Rappe
Rachel Foster	Scientist	UCSC
Dana Swift	Engineer	UW
Tobin Chen	Marine Technician	OTG
Kuhio Vellalos	Marine Technician	OTG

3.0. SUMMARY SCHEDULE

21 November	Pre-cruise meeting 1030 hrs.
29 November	Ship loading starting at 1200 hrs
30 November	Depart from Snug harbor at 0900 hrs. Science personnel on-board
	by 0800.
30 November	Station 1 Kahe Pt. operations.
1-3 December	Station ALOHA operations. Station 52 and Kaena CTD casts.
4 December	Arrive Snug harbor, ETA 0800 hrs, full offload

4.0. OPERATIONAL PLANS

4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 1000 lb. weight-test cast, one CTD cast to 1000 m, and a PRR cast (Sect. 4.2.7) will be conducted at this location in the afternoon of November 30. The CTD winch and crane will be required for these operations. After the operations are satisfactorily completed, the ship shall proceed to Station ALOHA.

4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the sediment traps will be deployed. Afterwards, one 200-m and one 1000-m casts will be conducted before deploying the AC9/Frrf (Sect. 4.2.8), and

Primary productivity array (Sect. 4.2.3). These operations will be followed by a near-bottom CTD cast.

4.2.2. Sediment trap array deployment

Upon arrival to Station ALOHA, the floating sediment traps will be deployed at a location within Station ALOHA, which will be determined by local current conditions to be determined enroute to ALOHA. The array will be deployed from the stern using the A-frame and our Sea-Mac winch. Power requirement for the winch is 440 VAC, three phase at 10 amps. After deployment we request that the Bridge verify that the radio transmitters are functioning and directionally correct.

The array will drift for about 53 hours before recovery. The array is equipped with 2 ARGOS satellite transmitters (platform #s 01833 and 03028), 2 strobe lights, and 2 radio transmitters (channel 74, 156.725 MHz). Daily positions of the array shall be transmitted by email directly to the ship (argosfix@km.soest.hawaii.edu, password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery.

After deployment of the sediment trap array, the ship shall return to the center of Station ALOHA to continue with CTD cast operations.

4.2.3 Primary production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (sunrise 0656 hrs on December 1), a free drifting incubation array will be deployed from the stern. We request the use of the A-frame for this operation and will also use the Sea-Mac winch. The array is equipped with one ARGOS satellite transmitter (platform # 60481, emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), strobe lights and a radio transmitter (channel 68, 156.425 MHz). The **ship shall keep within site of the array** while performing CTD operations for the last 6 hours of the approximately 12-hour time the array will be in the water. The array will be recovered just at sunset (1746 hrs). CTD operations shall continue after recovery. All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material.

4.2.4. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter sampling bottles. We need the ship's CTD winch and crane for this operation. Water samples for biogeochemical measurements will also be collected on each cast. The cast after the deployment of the primary productivity array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made continuously every 3 hours for a 36-hour period, ending with a second near-bottom cast. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0). To avoid disruptions in the schedule, this operation

should be coordinated with the chief scientist or the watch leaders (Susan Curless, Jefrey Snyder).

4.2.5. Gas Array deployment

A second free drifting incubation array will be deployed the third day of the cruise at ALOHA station. Samples for the gas array will be collected from cast 9. We request the use of the A-frame for the gas array deployment, and will also use the Sea-Mac winch. The array is equipped with one ARGOS satellite transmitter (platform # 08500, emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), a strobe light and a radio transmitter (channel 69, 156.475 MHz). The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 24 hours after its deployment. CTD operations shall continue after the recovery.

4.2.6. Zoo net tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled at around noon and two consecutive half-hour periods at midnight on the second, third, and fourth days (see schedule) with a total of eight available slots to accommodate cancellations due to sea state or other unforeseen problems. The A-frame and capstan will be needed for this operation. B. Watkins will be in charge of these operations.

4.2.7. Profiling Reflectance Radiometer (PRR).

Around noon on each day a profiling reflectance radiometer will be deployed from the main deck using the A-frame. The instrument is hand-lowered and retrieved with assistance from the winch.

4.2.8. AC9/FRRf

The Wet Labs AC9 is an optical instrument that measures water column spectral absorption and attenuation at nine wavelengths. The AC9 package also includes a Fast Repetition Rate Fluorometer (FRRf), and a Sea-Bird Seacat with temperature, conductivity, fluorometer, and pressure sensors. The package will be deployed to a target depth of 250 m at a constant speed of 10 m/min during the downcast and upcast. The A-frame and capstan will be needed for this operation.

4.3 Floating sediment trap recovery

In the morning of December 3, after the second deep cast has been completed, we shall transit for the recovery of the floating sediment trap array. The A-frame and the Sea-Mac winch will be needed to retrieve the sediment trap array. After the array is recovered, the ship shall transit to recover the Gas array. After the array is recovered, the ship shall transit to Station ALOHA to conduct one CTD cast, and two AC9/FRRf casts, after which the ship shall transit to Station 52 to conduct one CTD cast.

4.4 WHOTS Mooring (Station 52)

One 200-m CTD yo-yo cast will be conducted near the WHOTS mooring on December 3.. This cast should be conducted downwind, downcurrent, and at about 200 m from the mooring. The nominal position of the mooring is 22° 40.208'N, 157° 57.001'W. After the cast is completed, an ARGO float will be deployed from the stern before leaving to Station Kaena.

4.5. ARGO float deployment.

An ARGO free drifting float will be deployed from the stern before leaving station ALOHA. The deployment will be conducted by Dana Swift and it should take less than ½ hr.

4.6 Station Kaena (21° 50.8'N, 158° 21.8'W)

A near-bottom CTD cast (~2500 m) will be conducted at this location in the evening of December 3, after which the ship shall return to Snug harbor.

4.7 Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profiler (ADCP) will be in operation during the duration of the cruise. The OTG electronics technician will be in charge of the ADCP system.

4.8 Thermosalinograph and Fluorometer

The ship's thermosalinograph and fluorometer sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Snug harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The OTG electronics technician will be in charge of the thermosalinograph and fluorometer operations.

5.0 EQUIPMENT

5.1 The HOT science party shall be bringing the following

- 1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
- 2. Rosette and 24 12-1 water sampling bottles, all spare parts
- 3. One laboratory van with assorted equipment for radioisotope and general use
- 4. Distilled, deionized water and all required chemicals and isotopes
- 5. Storage van with assorted equipment (main deck)
- 6. Large vacuum waste container
- 7. Liquid nitrogen dewer
- 8. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights
- 9. Kevlar line, polypropylene line
- 10. Sediment traps and crosses
- 11. Drifting primary production array and gas array with light and radio transmitter, floats, weights, polypro. Line, spare buoy, etc.
- 12. PRR, AC-9/FRRf and other optical measuring instruments.
- 13. Large Sea-Mac winch (Mod. 1025 EHS). 60 Amp Hubbel plug/connector (440 VAC, 3 phase, 60 Amp breaker), and Kevlar line
- 14. Oxygen titration system
- 15. Plankton nets and towing lines
- 16. Desktop and laptop personal computers
- 17. Assorted tools
- 18. All required sampling bottles.
- 19. Deck incubation system
- 20. Pertinent MSDS

- 5.2. We will need the use of the following ship's equipment:
- 1. A-frame
- 2. A-frame block assembly
- 3. Appleton crane and winch with conducting wire for CTD
- 4. Electric power for winches (440 VAC, 3 phase, 60 Amp breaker) and vans (208 VAC single phase at 60 amps for labvan, 110 VAC 10 amps for equipment van)
- 5. Radio direction finder
- 6. Space on the main deck for one storage van
- 7. Space on upper deck for two lab vans port side
- 8. Space on upper deck for incubators
- 9. Hand-held VHF transceivers
- 10. Precision depth recorder
- 11. Shackles, sheaves, hooks and lines
- 12. Shipboard Acoustic Doppler Current Profiler
- 13. Thermosalinograph and Fluorometer
- 14. Copy machine
- 15. Grappling hooks and line
- 16. Navlink2 PC or equivalent
- 17. Running fresh water and seawater, hoses
- 18. Electronic mail system
- 19. GPS system
- 20. Uncontaminated seawater supply
- 21. Small capstan (~ 10 m/min)
- 22. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer
- 23. OTG's 24-place rosette, and 24 12-l water sampling bottles (to be used as spare)
- 24. Pinger (to be used as spare)
- 25. 1000 lb weight.
- 26. Remote CTD decibar pressure display in the winch operator cabin.

Ship: R/V KILO MOANA		HOT 197 CTD CASTS Nov. 30 – D	Nov. 30 – Dec. 4, 200	
	Cast	Samples #	Bottles	
Kahe l	Pt. 1000 m	O ₂ , Temp, DIC/Alk, Nuts, Chl a, LLN, LLPO ₄ , DOC, FCM, Salts	24	
Station	n ALOHA			
s2c1	200 m	CMORE(5@25, 5@45), MR (2@45), RF(4@10), SW(1@ 5,25,45,75,100,125,150,175)	24	
s2c2	1000 m	Primary Production, Salts, BL(2@25), SW(pb 5-75)	24	
s2c3	4740 m (PO-1)	O ₂ , Temp, DOC, DIC/Alk, Nuts, Salts	24	
s2c4	1000 m (PO-2)	O ₂ , Temp, Nuts, DIC/Alk, Quay, DOC, Salts	24	
s2c5	1000 m	PC/PN,CMORE(5@75, 5@125), Salts		
s2c6	1000 m	PPO4, RF(1@5,20,40), DV(3@10), Salts		
s2c7	1000 m	HPLC, Chl a, Slides, Salts		
s2c8	1000 m (BEACH)	O ₂ , Temp, DIC/Alk, Nuts, LLN, LLP,DOC, Keeling, Quay, Salts	23	
s2c9	1000 m	Gas Array (4@5, 25, 45, 75, 100, 125)	24	
s2c10	1000 m	Open, MR(1000,800,600,400,200,175,150,125,100,75,45,1 CMORE(5@ 770), Salts, BL(2@45, 75,100)	24	
s2c11	1000 m	PSi, MC(5,25,45,75,100,125,150,175), RF(1@5,20,40), Salts, DV(2@10), SW(pb MC profile)	23	
s2c12	1000 m	MIT, CMORE(5@500), Salts, BL(2@125)	24	
s2c13	1000 m	ATP, Quay(100,125,150,200,300), MC(200,300,500,770), MR(2@1000,2@500), Salts	24	
s2c14	1000 m	PE, Salts, MC(5,25,45,75,100,125,150,175), Quay(5,25,45,75), Salts		
2c15	1000 m	PUR CMORE(5@1000 5@200) Salts	24	

s2c10	1000 m	Open, MR(1000,800,600,400,200,175,150,125,100,75,45,10 CMORE(5@ 770), Salts, BL(2@45, 75,100)	
s2c11	1000 m	PSi, MC(5,25,45,75,100,125,150,175), RF(1@5,20,40), Salts, DV(2@10), SW(pb MC profile)	23
s2c12	1000 m	MIT, CMORE(5@500), Salts, BL(2@125)	24
s2c13	1000 m	ATP, Quay(100,125,150,200,300), MC(200,300,500,770), MR(2@1000,2@500), Salts	24
s2c14	1000 m	PE, Salts, MC(5,25,45,75,100,125,150,175), Quay(5,25,45,75), Salts	24
s2c15	1000 m	PUR, CMORE(5@1000, 5@200), Salts	24
s2c16	4740 m (PO-3)	Oxygen, Salts, MC(1000,2000,3000,4000), MR(4000,3000,2000,1000,800,600,400,175,125,100,75,10)	24
S2c16	1000 m	RF(4@10m), BL(<u>6@15</u>), Salinity substandard (<u>6@1000</u>), salts	19
WHO ' S52c1	FS Mooring 200 m	Salts RF(1@5,20,25,40,45,75), JE(6@15m)	15
Kaena S6c1	2400 m	Chl, Salts	13
		7	

SHIP R/V KILO MOANA

HOT 197 Date Nov. 30 - Dec. 4, 2007

		~	1	1	2007
TIME	Fri. 11/30	Sat. 12/1	Sun. 12/2	Mon. 12/3	Tue. 12/4
0000		S2C1			
0100			Net Tow		
0100		S2C2 PP	THEE TOW		
0200			S2C9 Gas		
			S2C) Gus	Transit sed traps	
0300		AC9/FRRF			
0400		Deploy PP Array	Deploy Gas Array		
0500		S2C3 PO-1	S2C10 Open	Recover traps Transit gas array	
0600				, , , , , , , , , , , , , , , , , , , ,	
0700				Recover gas array	
0800	Depart Snug		S2C11 PSi	Recover gas array	Arrive Snug
0800	Depart Shug		32011 131	Transit ALOHA	offload
0900					
1000		Net Tow	Net Tow	S2C17	
1100	Arrive Kahe (11:30) Weight cast	S2C4 PO-2 (Begin 36 hr)	S2C12 MIT	PRR AC9/FRRF	
1200	PRR	Net Tow	PRR AC9/FRRF	AC9/FRRF	
1300	S1C1	ATE	Net Tow	Transit St. 52	
1400	Transit ALOHA	S2C5 PC/PN	S2C13 ATP	S52C1	
1500				Deploy ARGO Transit St. Kaena	
1600					
1700		S2C6 PPO4	S2C14 PE		
1800		Recover PP array			
1900					
2000		S2C7 HPLC	S2C15 PUR		
2100				S6C1	
2200		Net Tow	Net Tow		
2300	Arrive ALOHA Deploy sed traps	S2C8 BEACH	S2C16 PO-3 (end 36 hours)	Transit Snug	

December 1: Sunrise 0656 Sunset 1746

6.0 HOT-197 Watch Schedule

0300-1500

Adriana Harlan - Water Boss

Lance Fujieki – - Alt Water Boss, Alt Tag

Brett Updyke - Tag

Jefrey Snyder - Watch Leader - Tag

Fernando Santiago-Mandujano - Chief Scientist, Console

1500-0300

Susan Curless - Watch Leader - Water Boss

Karin Bjorkman - Alt Tag

Tara Clemente – *Tag*

Paul Lethaby - Console

Justin Smith - Tag

At Large

Christin Shacat

Rachel Foster

Misty Miller

Naomi Wagoner

Dana Swift

Sam Wilson

Donn Viviani

Binglin Li

Blake Watkins

OTG

Tobin Chen

Kuhio Vellalos