

Hawaii Ocean Time-series HOT-218 Operational Cruise Plan

Cruise ID: KOK10-04

Vessel: R/V *Ka'Imikai-O-Kanaloa*, University of Hawaii

Master of the Vessel: Captain Ross Barnes

Chief Scientist: Susan Curless, University of Hawaii

OTG Marine Technicians: Kuhio Vellalos and Elly Speicher

Marine Center phone number: 842-9813

KOK phone number: 842-9818

KOK Cell number: 722-0839

Loading: February 12, 2010

Departure: February 15, 2010 @ **0800**

Arrival: February 19, 2010 @ 0800

1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Four stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at 21° 20.6'N, 158° 16.4'W and will be occupied on the first day of the cruise for about 2 hours.
- 2) Station 2, referred to as Station ALOHA is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied during the 2nd, 3rd, and 4th days of the cruise.
- 3) Station 52, the site of WHOTS Mooring, located at 22° 39.989'N, 157° 56.961'W will be occupied on the 4th day of the cruise for about one hour.
- 4) Station 6, referred to as Station Kaena, is located off Kaena Point at 21° 50.8'N, 158° 21.8'W and will be occupied on the 4th day of the cruise for about 2 hours.

1.1 SCIENTIFIC OPERATIONS

<u>Station</u>	<u>Activities</u>
Kahe (sta. 1)	Weight Cast, Hyperpro cast, CTD cast (1000 m)
ALOHA (sta. 2)	Sediment traps, gas array, net tows, CTD operations, primary productivity measurements, AC9, misc. experiments.
WHOTS mooring station (Sta. 52)	One CTD cast (yo-yo to 200 m).
Kaena (sta. 6)	One CTD cast (near-bottom)
Underway/continuous	ADCP, thermosalinograph, fluorometry, meteorology

2.0. SCIENCE PERSONNEL

Participant	Title	Affiliation/HOT Group
Karin Björkman	Marine Specialist	UH/BEACH
Daniela Böttjer	Post-doc	UH/BEACH
Susan Curless	Chief Scientist – Res. Assoc.	UH/BEACH
Ken Doggett	Research Associate	UH/CMORE
Lance Fujieki	Computer Specialist	UH/BEACH
Adriana Harlan	Research Associate	UH/BEACH
Kathryn Stanaway	Research Associate	UH/BEACH
Donn Viviani	Graduate Student	UH/BEACH
Blake Watkins	Marine Engineer	UH/BEACH
Asako Endo	Volunteer	UH/PO
Cameron Fumar	Research Associate	UH/PO
Rachel Mock	Volunteer	UH/PO
Bo Keopaseut	Research Associate	UH/PO
Fernando Santiago-Mandujano	Research Associate	UH/PO
Jefrey Snyder	Marine Technician	UH/PO
Qian (Lydia) Li	Graduate Student	UH
Dave Wisegarver	Technician	NOAA/PMEL
Lucia Upchurch	Technician	NOAA/PMEL
Elly Speicher	Marine Technician	OTG
Kuhio Vellalos	Marine Technician	OTG

3.0. SUMMARY SCHEDULE

8 February	Pre-cruise meeting 1330 hrs.
12 February	Ship loading starting at 0900 hrs.
15 February	Depart from Snug harbor at 0800 hrs. Science personnel on-board by 0700.
15 February	Station 1 Kahe Pt. operations.
15-18 February	Station ALOHA operations. Station 52 CTD casts. Station Kaena CTD cast.
19 February	Arrive Snug harbor. ETA 0800 hrs, full offload

4.0. OPERATIONAL PLANS

4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 500 lb. weight-test cast, one CTD cast to 1000 m and a Hyperpro cast (Sect. 4.2.7) will be conducted at this location on February 15th. The CTD winch and crane will be required for these operations. After the operations are satisfactorily completed, the ship shall proceed to Station ALOHA.

4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the sediment traps will be deployed. After the sediment trap deployment is complete, two 200-m and one 1000-m cast will be conducted before deploying the Primary Productivity array (Sect. 4.2.3). These operations will be followed by a near-bottom CTD cast.

4.2.2. Sediment trap array deployment

Upon arrival to Station ALOHA, the floating sediment traps will be deployed at a location within Station ALOHA, to be determined enroute to ALOHA by local current conditions. The array will be deployed from the stern rail using the small crane and the Sea-Mac winch. Power requirement for the winch is 440 VAC, three phase at 10 amps. After deployment we request that the Bridge verify that the radio transmitters are functioning and directionally correct.

The array will drift for about 53 hours before recovery. The array is equipped with 2 ARGOS satellite transmitters (platform #'s 01833, 60481), 2 strobe lights, and 2 radio transmitters (channel 72, 156.625 MHz). Daily positions of the array shall be transmitted by email directly to the ship (argosfix@satellite-email.com, password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery.

After deployment of the sediment trap array, the ship shall continue with CTD cast operations to prepare water for the Primary Productivity Array.

4.2.3 Primary production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (Sunrise 0703 hrs on February 16th), a free drifting incubation array will be deployed from the stern rail using the small crane and the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 03028, 60482, emailing positions to argosfix@satellite-email.com, password: argosfix), strobe lights and a radio transmitter (channel 68, 156.425 MHz). The **ship shall keep within site of the array** while performing CTD operations for the last 6 hours of the approximately 12-hour time the array will be in the water unless the array drifts outside of the ALOHA circle. If the array drifts out of the circle, the ship should return inside the circle to conduct CTD casts, and the monitoring of the array will be coordinated with the watch leader. The array will be recovered just at sunset (1829 hrs). CTD operations shall continue after recovery. All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material.

4.2.4. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter sampling bottles. We will need the ship's CTD winch and crane for these operations. Water samples for biogeochemical measurements will also be collected on each cast. The cast after the deployment of the primary productivity array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made continuously every 3 hours for a 36-hour period, ending with a second near-bottom cast. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0). To avoid disruptions in the schedule, this operation should be

coordinated with the chief scientist or the watch leaders (**Fernando Santiago-Mandujano, Jeffrey Snyder**).

4.2.5. Gas Array deployment

A second free drifting incubation array will be deployed the third day of the cruise at ALOHA station. Samples for the gas array will be collected from CTD cast 10. The gas array will be deployed from the stern rail using the small crane and the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 03028, 60482), emailing positions to argosfix@satellite-email.com, password: argosfix), a strobe light and a radio transmitter (channel 68, 156.425 MHz). The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 24 hours after its deployment. CTD operations shall continue after the recovery.

4.2.6. Zoo net tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled around noon and two consecutive half-hour periods at midnight on the second, third, and fourth days (see schedule) with a total of eight available slots to accommodate cancellations due to sea state or other unforeseen problems. The A-frame and capstan will be needed for this operation. B. Watkins will be in charge of these operations.

4.2.7. Hyperpro

The Hyperpro is a profiling unit with one up-looking and one down-looking hyperspectral radiometer, a WET Labs ECO-BB2F triplet (measuring Chlorophyll-a fluorescence and backscattering in the blue and red wavelengths), temperature and conductivity sensors. This instrument also incorporates a ship mounted surface radiometer. Around noon on the first, third and fourth days, the Hyperpro will be deployed from the stern rail using the small crane. The instrument is hand-lowered and retrieved with assistance from the winch.

4.2.8. ACS/AC9/FRRf/LISST

An optical package including a Wet Labs AC9 that measures water column spectral absorption and attenuation at nine wavelengths, a Chelsea Fast Repetition Rate Fluorometer (FRRf), a SeaBird Seacat with temperature, conductivity, fluorometer, and pressure sensors, and a LISST particle size and distribution analyzer will be deployed to a target depth of 200 m at a constant speed of 10 m/min during the downcast and upcast. The A-frame and capstan will be needed for this operation.

4.2.9. Automated Trace Element Sampler (ATE)

On the 2nd day of the cruise, the ATE will be hand deployed off the back deck to a depth of 10 m. The ATE will be recovered after 30 minutes in the water. The ATE is approximately 1' tall and 4'' in diameter, weighting 5 lbs.

4.3 Floating sediment trap recovery

In the morning of February 18th, after the AC9/FRRf cast has been completed, we shall transit for the recovery of the floating sediment trap array. The small crane and the Sea-Mac winch will be needed to retrieve the sediment trap array. After the array is recovered, the ship shall transit to recover the Gas Array. After the array is recovered, the ship shall transit to Station 52 conduct one 200 m yo-yo cast.

4.4 WHOTS-6 Mooring (Station 52)

One 200 m CTD cast shall be conducted near the WHOTS mooring on February 18th. The cast is to be a yo-yo cast with at least 6 full cycles. This cast should be conducted downwind, down current, and about 200 m from the mooring. The nominal position of the mooring is 22°39.989'N, 157°56.961'W.

After the yo-yo cast is completed, the ship shall transit to Station ALOHA to conduct one Hyperpro cast, and one AC9/FRRf cast. Once those operations are complete, the ship will transit to Station Kaena.

4.5 Station Kaena (21° 50.8'N, 158° 21.8'W)

A near-bottom CTD cast (~2500 m) will be conducted at this location in the evening of February 18th, after which the ship shall return to Snug harbor.

4.6 Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profiler (ADCP) will be in operation during the duration of the cruise. The OTG electronics technician will be in charge of the ADCP system.

4.7 Thermosalinograph and Fluorometer

The ship's thermosalinograph and fluorometer sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Snug harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The OTG technicians will be in charge of the thermosalinograph and fluorometer operations.

5.0 EQUIPMENT

5.1 The HOT science party shall be bringing the following

1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
2. Rosette and 24 12-l water sampling bottles, all spare parts
3. Three 20 ft. laboratory vans with assorted equipment for radioisotope and general use.
4. Distilled, deionized water and all required chemicals and isotopes
5. Large vacuum waste container
6. Liquid nitrogen dewar
7. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights
8. Kevlar line, polypropylene line
9. Sediment traps and crosses
10. Drifting primary production array and gas array with light and radio transmitter, floats, weights, polypro. Line, spare buoy, etc.
11. Hyperpro and other optical measuring instruments.
12. Oxygen titration system
13. Plankton nets and towing lines
14. Desktop and laptop personal computers
15. Assorted tools
16. All required sampling bottles
17. Deck incubation system
18. Pertinent MSDS

5.2. We will need the use of the following ship's equipment:

1. A-frame
2. A-frame block assembly
3. Crane and winch with conducting wire for CTD
4. Electric power for winches (440 VAC, 3 phase, 60 Amp breaker) and vans (208 VAC single phase at 60 amps for lab van, 110 VAC 10 amps for equipment van)
5. Radio direction finder
6. Space in the main deck hanger for one storage van
7. Space on upper deck for two 20ft lab vans
8. Space on upper deck for incubators
9. Hand-held VHF transceivers
10. Precision depth recorder
11. Shackles, sheaves, hooks and lines
12. Shipboard Acoustic Doppler Current Profiler
13. Thermosalinograph and Fluorometer
14. Copy machine
15. Grappling hooks and line
16. Navlink2 PC or equivalent
17. Running fresh water and seawater, hoses
18. Electronic mail system
19. GPS system
20. Uncontaminated seawater supply
21. Small capstan (~ 10 m/min)
22. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer
23. OTG's 24-place rosette, and 24 12-l water sampling bottles (to be used as spare)
24. 500 lb weight.
25. Remote CTD decibar pressure display in the winch operator cabin.
26. Large Sea-Mac winch (Mod. 1025 EHS). 60 Amp Hubbel plug/connector (440 VAC, 3 phase, 60 Amp breaker)
27. Monitor in Rock Lab displaying ship coordinates and GMT.
28. Seapoint fluorometer (to be used as a spare)

Cast	Samples	#Bottles
<u>Kahe Pt.</u>		
s1c1	1000 m O ₂ , Temp, DIC/Alk, Nuts, Chl a, LLN, LLPO ₄ , DOC, FCM, DW (pb O ₂ depths), QL(pb@5,45,75,100,125,200,1000), Salts	24
<u>Station ALOHA</u>		
s2c1	200 m CMORE(5@25,5@45,5@75)	15
s2c2	1000 m Primary Production, (KD pb PP depths), Salts	22
s2c3	200 m DB (18@5m)	18
s2c4	4740 m (PO-1) O ₂ , Temp, DOC, DIC/Alk, Nuts, Salts, DW (pb O ₂ depths)	24
s2c5	1000 m (PO-2) O ₂ , Temp, Nuts, DIC/Alk, DOC, Salts, DW (pb O ₂ depths)	24
s2c6	1000 m PC/PN, QL(1@5,45,75,100,125,200,1000), Salts	20
s2c7	1000 m PPO ₄ , QL(1@5,45,75,100,125,200), Salts	20
s2c8	1000 m (BEACH) O ₂ , Temp, DIC/Alk, Nuts, LLN, LLP,DOC, Keeling, Quay, Salts DW (pb O ₂ depths)	23
s2c9	1000 m PUR, CMORE(5@1000,5@770,5@500), Salts	24
s2c10	1000 m Gas Array (2@5,25,45,75,100,125), Salts	14
s2c11	1000 m CMORE(5@125,5@200), Salts	12
s2c12	1000 m PSi, MC(5,25,45,75,100,125,150,175), Salts QL(1@200, pb@5,45,75,100,125)	19
s2c13	1000 m MIT, Salts	10
s2c14	1000 m ATP, MC(200,300,500,770), Salts	15
s2c15	1000 m PE, MC(5,25,45,75,100,125,150,175), Salts	22
s2c16	1000 m HPLC, Chl a, Slides, Salts	22
s2c17	4740 m (PO-3) Oxygen, MC(1000,2000,3000,4000), DW(pb O ₂ Depths), Salts DV(1@4800,4750)	14
<u>WHOTS Mooring</u>		
s52c1	200 m yo-yo BC(1@15,40,70), QL(1@5,45,75,100,125,200)	9
<u>Kaena</u>		
s6c1	2400 m Chl, Salts	13

MC=Matt Church, DW=Dave Wisegarver, BC=Brandon Carter, QL=Qian Li, KD=Ken Doggett,
DB=Daniela Böttjer, DV=Donn Viviani

TIME	Mon. 2/15	Tues. 2/16	Wed. 2/17	Thurs. 2/18	Fri. 2/19
0000		Arrive ALOHA Deploy sed traps			
0100		S2C1	Net Tow		
0200		S2C2 PP	S2C10 Gas		
0300		S2C3		AC9/FRRF	
0400		Deploy PP Array	Deploy Gas Array	Transit sed traps	
0500		S2C4 PO-1	S2C11 Open		
0600				Recover traps Transit gas array	
0700				Recover gas array	
0800	Depart Snug		S2C12 PSi	Transit St. 52	Arrive Snug
0900				S52C1 WHOTS	
1000	Arrive Kahe (10:30) Weight cast	Net Tow	Net Tow	Transit St. ALOHA	
1100	Hyperpro	S2C5 PO-2 (Begin 36 hr)	S2C13 MIT	AC9/FRRF	
1200	S1C1	Net Tow	Hyperpro AC9/FRRF	Hyperpro	
1300	Transit ALOHA	ATE			
1400		S2C6 PC/PN	S2C14 ATP		
1500				Transit St. Kaena	
1600					
1700		S2C7 PPO4	S2C15 PE		
1800		Recover PP array			
1900					
2000		S2C8 BEACH	S2C16 HPLC		
2100				S6C1	
2200		Net Tow	Net Tow		
2300		S2C9 PUR	S2C17 PO-3 (end 36 hours)	Transit Snug	

February 16: Sunrise 0703, Sunset 1829

6.0 HOT-218 Watch Schedule

0300-1500

Adriana Harlan – *Water Boss*

Lance Fujieki – *Tag*

Donn Viviani – *Tag*

Jefrey Snyder – *Watch Leader - Console*

Cameron Fumar – *Alt Tag*

Rachel Mock

1500-0300

Susan Curless – *Chief Scientist - Water Boss*

Kathryn Stanaway – *Tag*

Bo Keopaseut – *Tag*

Fernando Santiago-Mandujano – *Watch Leader - Console*

Asako Endo

0900-2100

Karin Björkman – *Alt Tag*

At Large

Daniela Böttjer

Blake Watkins

Ken Doggett – *Alt Tag*

Lucia Upchurch

Dave Wisegarver

Qian Li

OTG

Elly Speicher – *Deck Boss*

Kuhio Vellalos – *Deck Boss*