

Hawaii Ocean Time-series HOT-223 Operational Cruise Plan

Cruise ID: KM-1012

Vessel: R/V *Kilo Moana*, University of Hawaii

Master of the Vessel: Captain Ross Barnes

Chief Scientist: Susan Curless, University of Hawaii

OTG Marine Technicians: Justin Smith, Ben Colello

Kilo Moana phone number: 842-9817, cell # 864-0065

Marine Center phone number: 842-9813

Loading: July 6, 2010 @ 0900

Departure: July 7, 2010 @ 0800

Arrival: July 11, 2010 @ 0800

****Warning - Navigational and array deployment hazard. ****

HOT Profiler Mooring- To be deployed at Station ALOHA early July, 2010

This mooring's nominal location is **22° 44.88'N 158° 1.58'W**, approximately 1.5 miles WSW of the center of Station ALOHA. It has a small surface tether telemetry marker buoy and an instrument platform 80 m below the surface. This area of the circle should be avoided.

1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Four stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at 21° 20.6'N, 158° 16.4'W and will be occupied on the first day of the cruise for about 2 hours.
- 2) Station 2, referred to as Station ALOHA, is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied during the 2nd, 3rd, and 4th days of the cruise.
- 3) Station 52, the site of WHOTS Mooring, located at 22° 39.989'N, 157° 56.961'W will be occupied on the 4th day of the cruise for about one hour.
- 4) Station 6, referred to as Station Kaena, is located off Kaena Point at 21° 50.8'N, 158° 21.8'W and will be occupied on the 4th day of the cruise for about 2 hours.

1.1 SCIENTIFIC OPERATIONS

<u>Station</u>	<u>Activities</u>
Kahe (sta. 1)	Weight Cast, Hyperpro cast, CTD cast (1000 m)
ALOHA (sta. 2)	Sediment traps, gas array, net tows, CTD operations, primary productivity measurements, AC9/FRRf, misc. experiments
WHOTS mooring station (Sta. 52)	One CTD cast (yo-yo to 200 m).
Kaena (sta. 6)	CTD cast (near bottom)
Underway/continuous	ADCP, thermosalinograph, pCO ₂ system, fluorometry, and meteorology

2.0. SCIENCE PERSONNEL

Participant	Title	Affiliation/HOT Group
Daniela Böttjer	Post-doc	UH/CMORE
Susan Curless	Chief Scientist – Res. Assoc.	UH/BEACH
Lance Fujieki	Computer Specialist	UH/BEACH
Adriana Harlan	Research Associate	UH/BEACH
Dan Sadler	Research Associate	UH/BEACH
Donn Viviani	Graduate Student	UH/BEACH
Brenner Wai	Technician	UH/CMORE
Blake Watkins	Marine Engineer	UH/BEACH
Cameron Fumar	Research Associate	UH/PO
Bo Keopaseut	Research Associate	UH/PO
Paul Lethaby	Research Associate	UH/PO
Jefrey Snyder	Marine Technician	UH/PO
Craig Nosse	Research Associate	UH/PO
Didier Dumas	Graduate Student	UH/PO
Jim Foley	Marine Educator	UH/CMORE
Chris Schvarcz	Graduate Student	UH
Qian (Lydia) Li	Graduate Student	UH
Lydia Baker	Graduate Student	UH/CMORE
Daniela del Valle	Post-doc	UH/BEACH
Kiara Kealoha	Intern	CMORE
Bruce Howe	Scientist	UH
Jennie Mowatt	Technician	UH
Kiminori Shitashima	Scientist	CRIEPI/Japan
Justin Smith	Marine Technician	OTG
Ben Colello	Marine Technician	OTG

3.0. SUMMARY SCHEDULE

25 June	Pre-cruise meeting, MSB 307, 1300 hrs.
6 July	Ship loading starting at 0900 hrs.
7 July	Depart from Snug harbor at 0800 hrs. Science personnel on-board by 0700.
7 July	Station 1 Kahe Pt. operations.
7-10 July	Station ALOHA operations. Station 52 and Kaena CTD casts.
11 July	Arrive back to Snug harbor. ETA 0800 hrs, full offload.

4.0. OPERATIONAL PLANS

4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 1000 lb. weight-test cast, one CTD cast to 1000 m, and a Hyperpro cast (Sect. 4.2.7) will be conducted at this location on July 7th. The A-frame, Sea-Mac winch, CTD crane and CTD winch will be required for these operations. After the operations are satisfactorily completed, the ship shall proceed to Station ALOHA.

4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the sediment traps will be deployed. After the sediment trap deployment is complete, two 200-m and one 1000-m cast will be conducted before deploying the Primary Productivity array (Sect. 4.2.3). These operations will be followed by a near-bottom CTD cast.

4.2.2. Sediment trap array deployment

Upon arrival to Station ALOHA, the floating sediment traps will be deployed at a location within Station ALOHA, to be determined enroute to ALOHA by local current conditions. The array will be deployed from the stern, using the A-frame and Sea-Mac winch. Power requirement for the winch is 440 VAC, three phase at 10 amps. After deployment we request that the Bridge verify that the radio transmitters are functioning and directionally correct.

The array will drift for about 53 hours before recovery. The array is equipped with 2 ARGOS satellite transmitters (platform #'s 01833, 60481), 2 strobe lights, and 2 radio transmitters (channel 72, 156.625 MHz). Daily positions of the array shall be transmitted by email directly to the ship (argosfix@km.soest.hawaii.edu, password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery.

After deployment of the sediment trap array, the ship shall continue with CTD cast operations to prepare water for the Primary Productivity Array.

4.2.3 Primary production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (sunrise 0553 hrs on July 8th), a free drifting incubation array will be deployed from the stern. We request the use of the A-frame for this operation and will also use the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 03028, 60482, emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), strobe lights and a radio transmitter (channel 68, 156.425 MHz). The **ship shall keep within site of the array** while performing CTD operations for the last 6 hours of the approximately 12-hour time the array will be in the water unless the array drifts outside of the ALOHA circle. If the array drifts out of the circle, the ship should return inside the circle to conduct CTD casts, and the monitoring of the array will be coordinated with the watch leader. The array will be recovered just at sunset (1921 hrs). CTD operations shall continue after recovery. All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material.

4.2.4. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter sampling bottles. We will need the ship's CTD winch and crane for these operations. Water samples for biogeochemical measurements will also be collected on each cast. The cast after the deployment of the primary productivity array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made continuously every 3 hours for a 36-hour period, ending with a second near-bottom cast. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0). To avoid disruptions in the schedule, this operation should be coordinated with the chief scientist or the watch leaders (**Dan Sadler, Paul Lethaby**).

4.2.5. Gas Array deployment

A second free drifting incubation array will be deployed the third day of the cruise at ALOHA station. Samples for the gas array will be collected from CTD cast 10. We request the use of the A-frame for this operation and will also use the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 03028, 60482), emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), a strobe light and a radio transmitter (channel 68, 156.425 MHz). The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 24 hours after its deployment. Assistance from the bridge is requested in plotting the drift track of the array. CTD operations shall continue after the deployment.

4.2.6. Zoo net tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled around noon and midnight on the second, third, and fourth days (see schedule) for a total of six slots. The A-frame and capstan will be needed for this operation. B. Watkins will be in charge of these operations.

4.2.6.1 Hand net tows

A small 20 um net will be deployed off the stern to a depth of 25 m for about 15-20 minutes at various times during the cruise. The ships deck equipment is not needed for this operation. We request that the ship remain stationary during these tows. C.Schvarcz and L.Baker will be conducting these tows.

4.2.7. Hyperpro

The Hyperpro is a profiling unit with one up-looking and one down-looking hyperspectral radiometer, a WET Labs ECO-BB2F triplet (measuring Chlorophyll-a fluorescence and backscattering in the blue and red wavelengths), temperature and conductivity sensors. This instrument also incorporates a ship mounted surface radiometer. Around noon on the first, third and fourth days, the Hyperpro will be deployed from the stern rail using the small crane. The instrument is hand-lowered and retrieved with assistance from the winch.

4.2.8. ACS/AC9/FRRf/LISST

An optical package including a Wet Labs AC9 that measures water column spectral absorption and attenuation at nine wavelengths, a Chelsea Fast Repetition Rate Fluorometer (FRRf), a SeaBird Seacat with temperature, conductivity, fluorometer, and pressure sensors, and a LISST particle size and distribution analyzer will be deployed to a target depth of 200 m at a constant speed of 10 m/min during the downcast and upcast. The A-frame and capstan will be needed for this operation.

4.2.9. Automated Trace Element Sampler (ATE)

On the 2nd day of the cruise, the ATE will be hand deployed off the back deck to a depth of 10 m. The ATE will be recovered after 30 minutes in the water. The ATE is approximately 1' tall and 4'' in diameter, weighting 5 lbs.

4.3 Floating sediment trap recovery

In the morning of July 10th, after the AC9/FRRf cast has been completed, we shall transit for the recovery of the floating sediment trap array. The A-frame and the Sea-Mac winch will be needed to retrieve the sediment trap array. After the array is recovered, the ship shall transit to recover the Gas Array. After the array is recovered, the ship shall transit to Station 52 conduct one 200 m yo-yo cast.

4.4 WHOTS-6 Mooring (Station 52)

One 200-m CTD yo-yo cast with at least 6 full cycles will be conducted near the WHOTS mooring on July 10th. This cast should be conducted downwind, downcurrent, and about 200 m from the mooring. The nominal position of the mooring is 22°39.989'N, 157°56.961'W.

After these operations are completed, the ship shall transit to Station ALOHA to conduct one Hyperpro cast, one AC9/FRRf cast. Once those operations are complete, and if weather allows, the Sea Glider deployment operation shall commence.

4.5 Sea Glider #147 and #146 Deployment

Two hours of time is required for deploying a sea glider. Approximately 30 minutes will be needed to deploy a Sea Glider using the winch and the ship's A frame. Once the glider is in the water, it will conduct a shallow test dive (~30 min) and call its operational status into the command center.

It is requested that during the test dive, the ship stays close to the deployment site until the status of the glider has been confirmed to be operational. One hour has been scheduled for small boat operations for the recovery of the glider should it malfunction during the test dive.

There are three scheduled time slots for Sea Glider deployment attempts. Deployment will not be attempted unless the weather conditions are safe for launching the small boat. It will be at the Captain's discretion if these operations are able to be completed.

4.6 Station Kaena (21° 50.8'N, 158° 21.8'W)

A near-bottom CTD cast (~2500 m) will be conducted at this location in the evening of July 26th, after which the ship shall return to Snug harbor.

4.7 Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profiler (ADCP) will be in operation during the duration of the cruise. The OTG electronics technician will be in charge of the ADCP system.

4.8 Thermosalinograph, $p\text{CO}_2$ system, and Fluorometer

The ship's thermosalinograph, $p\text{CO}_2$ system and fluorometer sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Snug harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The OTG technicians will be in charge of the thermosalinograph and fluorometer operations.

5.0 EQUIPMENT

5.1 The HOT science party shall be bringing the following

1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
2. Rosette and 24 12-l water sampling bottles, all spare parts
3. Two 20 ft. laboratory vans with assorted equipment for radioisotope and general use.
4. Distilled, deionized water and all required chemicals and isotopes
5. Large vacuum waste container
6. Liquid nitrogen dewar
7. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights
8. Kevlar line, polypropylene line
9. Sediment traps and crosses
10. Drifting primary production array and gas array with light and radio transmitter, floats, weights, polypro. line, spare buoy, etc.
11. Hyperpro and other optical measuring instruments.
12. Oxygen titration system

13. Plankton nets and towing lines
14. One equipment van to be located on the main deck.
14. Desktop and laptop personal computers
15. Assorted tools
16. All required sampling bottles
17. Deck incubation system
18. Pertinent MSDS
19. Iridium handset and other pertinent items needed for sea glider operations.

5.2. We will need the use of the following ship's equipment:

1. A-frame
2. A-frame block assembly
3. Caley Crane and winch with conducting wire for CTD
4. Electric power for winches (440 VAC, 3 phase, 60 Amp breaker) and vans (208 VAC single phase at 60 amps for labvan, 110 VAC 10 amps for equipment van)
5. Radio direction finder
6. Space on the main deck for one equipment van
7. Space on upper deck for three laboratory vans
8. Space on upper deck for incubators
9. Hand-held VHF transceivers
10. Precision depth recorder
11. Shackles, sheaves, hooks and lines
12. Shipboard Acoustic Doppler Current Profiler
13. Thermosalinograph, $p\text{CO}_2$ system, and Fluorometer
14. Copy machine
15. Grappling hooks and line
16. Navlink2 PC or equivalent
17. Running fresh water and seawater, hoses
18. Electronic mail system
19. GPS system
20. Uncontaminated seawater supply
21. Small capstan (~ 10 m/min)
22. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer, $p\text{CO}_2$
23. OTG's 24-place rosette, and 24 12-l water sampling bottles (to be used as spare)
24. 1000 lb weight.
25. Large Sea-Mac winch (Mod. 1025 EHS). 60 Amp Hubbel plug/connector (440 VAC, 3 phase, 60 Amp breaker)
26. OTG's radiation van
27. Seapoint fluorometer (to be used as a spare)

Cast	Depth	Samples	#Bottles
<u>Kahe Pt.</u>			
s1c1	1000 m	O ₂ , Temp, DIC/Alk, Nuts, Chl a, LLN, LLPO ₄ , DOC, FCM, Salts QL(pb@5,45,75,100,125,200)	24
<u>Station ALOHA</u>			
s2c1	200 m	DB (18@5m), QL(1@5,45,75,100,125,200)	24
s2c2	1000 m	Primary Production, DV(pb on PP depths), Salts	24
s2c3	200 m	CMORE(5@25,5@45,5@75), DdV(2@25)	17
s2c4	4740 m (PO-1)	O ₂ , Temp, DOC, DIC/Alk, Nuts, Salts	24
s2c5	1000 m (PO-2)	O ₂ , Temp, Nuts, DIC/Alk, DOC, Salts, LB(pb@DCM)	24
s2c6	1000 m	PC/PN, LB(1@5,50,100), QL(1@200,150 pb@100,75,45,5), Salts	20
s2c7	1000 m	PPO ₄ , QL(1@5,45,75,100,125,200), CS(1@25,50,75,100), Salts	20
s2c8	1000 m (BEACH)	O ₂ , Temp, DIC/Alk, Nuts, LLN, LLP,DOC, Keeling, Quay, Salts	23
s2c9	1000 m	PUR, CMORE(5@1000,5@770,5@500), Salts	24
s2c10	1000 m	Gas Array(2@5,25,45,75,100,125), DV(pb on all depths), Salts	14
s2c11	1000 m	CMORE(5@125,5@200), PO(12@1000), Salts	24
s2c12	1000 m	PSi, MC(5,25,45,75,100,125,150,175), LB(1@5,50,100), QL(1@200, pb@5,45,75,100,125), Salts	22
s2c13	1000 m	MIT, LB(1@DCM), DV(1@25,75) DV(pb@5,45,100,125), Salts	13
s2c14	1000 m	ATP, SW(1@200,300,400,500, 600,700,800,900,1000), MC(200,300,500,770), DdV(2@25), Salts	24
s2c15	1000 m	PE, MC(5,25,45,75,100,125,150,175), SW(pb MC), Salts	22
s2c16	1000 m	HPLC, Chl a, Slides, Salts	22
s2c17	4740 m (PO-3)	Oxygen, MC(1000,2000,3000,4000), DV(1@4800,4750), Salts	23
s2c18	200 m	CS (19@25), LB(1@DCM), DdV(2@25)	22
<u>WHOTS Mooring</u>			
S50c1	200 m yo-yo	QL(1@5,45,75,100,125,200), LB(1@5,50,100)	9
<u>Kaena</u>			
S6c1	2400 m	Chl, Salts	13

MC=Matt Church, SW=Sam Wilson, CS=Chris Schvarcz, DB=Daniela Böttjer, DV=Donn Viviani,
DdV= Daniella de Valle, QL=Lydia Li, LB=Lydia Baker

TIME	Wed. 7/7	Thur. 7/8	Fri. 7/9	Sat. 7/10	Sun. 7/11
0000		S2C1			
0100		S2C2 PP	Net Tow		
0200			S2C10 Gas		
0300		S2C3		AC9/FRRF	
0400		Deploy PP Array	Deploy Gas Array	Transit sed traps	
0500		S2C4 PO-1	S2C11 Open	Recover traps Transit gas array	
0600			Deploy Sea Glider	Recover gas array	
0700				Transit St. 52	
0800	Depart Snug		S2C12 PSi	S52C1 WHOTS	Arrive Snug
0900				Transit St. ALOHA	
1000	Arrive Kahe (10:30) Weight cast	Net Tow Hand Net (LB)	Net Tow Hand Net (CS)	S2C18	
1100	Hyperpro	S2C5 PO-2 (Begin 36 hr)	S2C13 MIT	AC9/FRRF	
1200	S1C1	Net Tow	Hyperpro AC9/FRRF	Hyperpro Deploy Sea Glider	
1300	Transit ALOHA	ATE			
1400		S2C6 PC/PN	S2C14 ATP		
1500			Deploy Sea Glider	Transit St. Kaena	
1600					
1700		S2C7 PPO4	S2C15 PE		
1800					
1900		Recover PP array			
2000		S2C8 BEACH	S2C16 HPLC		
2100				S6C1	
2200		Net Tow	Net Tow		
2300	Arrive ALOHA Deploy sed traps	S2C9 PUR	S2C17 PO-3 (end 36 hours)	Transit Snug	

July 8: Sunrise 0553, Sunset 1921

6.0 HOT-223 Watch Schedule

0300-1500

Adriana Harlan - *Water Boss*
Dan Sadler - *Watch Leader - Tag*
Lance Fujieki - *Alt Tag*
Jefrey Snyder - *Console*
Cameron Fumar - *Alt Tag*
Craig Nosse - *Tag*

1500-0300

Susan Curless - *Chief Scientist - Water Boss*
Brett Updyke - *Alt Tag*
Paul Lethaby - *Watch Leader - Console*
Bo Keopaseut - *Tag*
Didier Dumas - *Tag*

0900-2100

Jim Foley
Lydia Baker

At Large

Lydia Li
Blake Watkins
Donn Viviani - *Alt Tag*
Daniela Böttjer
Bruce Howe
Jennie Mowatt
Kiminori Shitashima
Daniela del Valle
Brenner Wai - *Alt Tag*
Chris Schvarcz
Kiara Kealoha

OTG

Justin Smith
Ben Colello