

Hawaii Ocean Time-series HOT-229 Operational Cruise Plan

Cruise ID: KM 11-02A

Vessel: R/V *Kilo Moana*, University of Hawaii

Master of the Vessel: Captain Gray Drewry

Chief Scientist: Craig Nosse, University of Hawaii

OTG Marine Technicians: Dan Fitzgerald and Vic Polidoro

Kilo Moana phone number: 842-9817, cell # 864-0065, satellite # 001-870-336-956510

Marine Center phone number: 842-9813

Loading: January 26, 2011 @ 0900

Departure: January 27, 2011 @ 0900

Arrival: January 30, 2011 @ 1500

****Warning - Navigational and array deployment hazard. ****

HOT Profiler Mooring (HPM)- Deployed at Station ALOHA October 2010

This mooring's nominal location is **22° 44.800'N 158° 01.455'W**, approximately 1.5 miles WSW of the center of Station ALOHA. It has a small surface tether telemetry marker buoy and an instrument platform 80 m below the surface. There have been reports that **the marker buoy may be submerged beneath the surface**. This area of the circle should be avoided.

1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Three stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at 21° 20.6'N, 158° 16.4'W and will be occupied on the first day of the cruise for about 2 hours.
- 2) Station 2, referred to as Station ALOHA, is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied during the 2nd, 3rd, and 4th days of the cruise.
- 3) Station 50, the site of WHOTS-7 Mooring, approximate position 22° 46.0052'N 157° 53.9897'W will be occupied on the 4th day of the cruise for about one hour.

Station 6, referred to as Station Kaena, which has been occupied regularly during recent HOT cruises, will not be occupied during this cruise so that we may return to port on the afternoon of 30 January and allow the following cruise aboard *Kilo Moana* more time to load.

1.1 SCIENTIFIC OPERATIONS

<u>Station</u>	<u>Activities</u>
Kahe (sta. 1)	Weight Cast, Hyperpro cast, CTD cast (1000 m), Niskin cast.
ALOHA (sta. 2)	Sediment traps, gas array, net tows, CTD operations, primary productivity measurements, ACS/AC9/FRRf, misc. experiments
WHOTS mooring station (Sta. 50)	One CTD cast (yo-yo to 200 m), surface instrument intercomparisons.
Underway/continuous	ADCP, thermosalinograph, pCO ₂ system, fluorometry, and meteorology

2.0. SCIENCE PERSONNEL

Participant	Title	Affiliation/HOT Group
Susan Curless	Research Associate	UH/BEACH
Lance Fujieki	Computer Specialist	UH/BEACH
Adriana Harlan	Research Associate	UH/BEACH
Dan Sadler	Research Associate	UH/BEACH
Brett Updyke	Research Associate	UH/BEACH
Donn Viviani	Graduate Student	UH/BEACH
Scott Grant	Graduate Student	UH/CMORE
Blake Watkins	Marine Engineer	UH/BEACH
Cameron Fumar	Research Associate	UH/PO
Bo Keopaseut	Research Associate	UH/PO
Jefrey Snyder	Marine Technician	UH/PO
Craig Nosse	Research Associate	UH/PO
Dan Fitzgerald	Marine Technician	OTG
Vic Polidoro	Marine Technician	OTG

3.0. SUMMARY SCHEDULE

26 January	Ship loading at 0900 hrs.
27 January	Depart from Snug harbor at 0900 hrs. Science personnel on-board by 0800.
27 January	Station 1 Kahe Pt. operations.
27-30 January	Station ALOHA operations. Station 50 CTD yo-yo cast.
30 January	Arrive back to Snug Harbor. ETA 1500 hrs, full offload.

4.0. OPERATIONAL PLANS

4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 1000 lb. weight-test cast, one CTD cast to 1000 m, and a Hyperpro cast (Sect. 4.2.7) will be conducted at this location on January 27th. The A-frame, Sea-Mac winch, CTD crane and CTD winch will be required for these operations.

4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the sediment traps will be deployed. After the sediment trap deployment is complete, one 200-m and one 1000-m cast will be conducted before deploying the Gas Array (Sect. 4.2.3). These operations will be followed by a near-bottom CTD cast.

4.2.2. Sediment trap array deployment

Upon arrival to Station ALOHA, the floating sediment traps will be deployed at a location within Station ALOHA, to be determined enroute to ALOHA by local current conditions. The array will be deployed from the stern, using the A-frame and Sea-Mac winch. Power requirement for the winch is 440 VAC, three phase at 10 amps. After deployment we request that the Bridge verify that the radio transmitters are functioning and directionally correct.

The array will drift for about 50 hours before recovery. The array is equipped with 2 ARGOS satellite transmitters (platform #'s 01833, 60481), 2 strobe lights, and 2 radio transmitters (channel 72, 156.625 MHz). Daily positions of the array shall be transmitted by email directly to the ship

(argosfix@km.soest.hawaii.edu, password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery.

After deployment of the sediment trap array, the ship shall continue with CTD cast operations to prepare water for the Gas Array.

4.2.3 Gas Array deployment

A free drifting incubation array will be deployed the second day of the cruise at ALOHA station. Samples for the gas array will be collected from Station 2 CTD cast 2. We request the use of the A-frame for this operation and will also use the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 60484, 84857), emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), a strobe light and a radio transmitter (channel 74, 156.725 MHz). The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 25 hours after its deployment. Assistance from the bridge is requested in plotting the drift track of the array. A near-bottom CTD cast shall be conducted after the deployment.

4.2.4. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter Bullister sampling bottles. We will need the ship's A-frame and trawl winch (outfitted with 0.681 wire) for these operations. Water samples for biogeochemical measurements will be collected on each CTD cast. The cast after the deployment of the gas array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made continuously every 3 hours for a 36-hour period. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0). To avoid disruptions in the schedule, this operation should be coordinated with the chief scientist or the watch leaders (**Susan Curless, Jeffrey Snyder**).

4.2.5. Primary Production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (sunrise 0710 hrs on January 29th), a free drifting incubation array will be deployed from the stern. We request the use of the A-frame for this operation and will also use the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 60484, 84857, emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), strobe lights and a radio transmitter (channel 74, 156.725 MHz). The **ship shall keep within site of the array** while performing CTD operations for the last 6 hours of the approximately 12-hour time the array will be in the water unless the array drifts outside of the ALOHA circle. If the array drifts out of the circle, the ship should return inside the circle to conduct CTD casts, and the monitoring of the array will be coordinated with the watch leader. The array will be recovered just at sunset (1820 hrs). CTD operations shall continue after recovery. All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material.

4.2.6. Zoo net tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled around noon and midnight on the second, third, and fourth days (see

schedule) for a total of six slots. The A-frame and capstan will be needed for this operation. B. Watkins will be in charge of these operations.

4.2.7. Hyperpro

The Hyperpro is a profiling unit with one up-looking and one down-looking hyperspectral radiometer, a WET Labs ECO-BB2F triplet (measuring Chlorophyll-a fluorescence and backscattering in the blue and red wavelengths), temperature and conductivity sensors. This instrument also incorporates a ship mounted surface radiometer. Around noon on the first and third days, the Hyperpro will be deployed from the stern through a small block hung from the A-frame. The instrument is hand-lowered and retrieved with assistance from the winch.

4.2.8. ACS/AC9/FRRf/LISST

An optical package including a Wet Labs AC9 that measures water column spectral absorption and attenuation at nine wavelengths, a Chelsea Fast Repetition Rate Fluorometer (FRRf), a SeaBird Seacat with temperature, conductivity, fluorometer, and pressure sensors, and a LISST particle size and distribution analyzer will be deployed to a target depth of 200 m at a constant speed of 10 m/min during the downcast and upcast. The A-frame and capstan will be needed for this operation.

4.2.9. Automated Trace Element Sampler (ATE)

On the 2nd day of the cruise, the ATE will be hand deployed off the back deck to a depth of 10 m. The ATE will be recovered after 30 minutes in the water. The ATE is approximately 1' tall and 4'' in diameter, weighing 5 lbs.

4.3 Station 50 - WHOTS-7 Mooring

(nominal position of mooring = 22° 46.0052'N 157° 53.9897'W)

4.3.1 CTD yo-yo cast (subsurface instrument intercomparison)

One 200-m CTD yo-yo cast with at least 6 full cycles will be conducted near the WHOTS mooring on January 30th for subsurface instrument intercomparisons. This cast should be conducted downwind, downcurrent, and about 200 m from the mooring.

4.3.2 Surface instrument intercomparison

While on station, the ship's meteorological system shall be in operation for surface instrument intercomparisons with the WHOTS mooring.

Once the yo-yo cast is completed, the ship shall transit to recover the sediment trap array.

4.4 Floating sediment trap recovery

In the early morning of January 30th, after the WHOTS yo-yo cast has been completed, we shall transit for the recovery of the floating sediment trap array. The A-frame and the Sea-Mac winch will be needed to retrieve the sediment trap array. After the array is recovered, the ship shall transit to Honolulu

4.5 Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profiler (ADCP) will be in operation during the duration of the cruise. The OTG electronics technicians will be in charge of the ADCP system.

4.6 Thermosalinograph, $p\text{CO}_2$ system, Fluorometer, and meteorological system

The ship's thermosalinograph, $p\text{CO}_2$ system and fluorometer sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Snug Harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The ship's meteorological

system shall be in operation throughout the cruise. Access to real-time underway data through the ship's network will be required. The OTG technicians will be in charge of the thermosalinograph, $p\text{CO}_2$ system, Fluorometer, and meteorological suite operations.

5.0 EQUIPMENT

5.1 The HOT science party shall be bringing the following

1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
2. Rosette and 24 12L Bullister sampling bottles, all spare parts
3. One 20 ft. laboratory vans with assorted equipment for radioisotope and general use ("23" Van,)
4. One 12 ft. equipment van ("Blue" Van)
5. Distilled, deionized water and all required chemicals and isotopes
6. Large vacuum waste container
7. Liquid nitrogen dewar
8. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights
9. Kevlar line, polypropylene line
10. Sediment traps and crosses
11. Drifting primary production array and gas array with light and radio transmitter, floats, weights, polypro. line, spare buoy, etc.
12. Hyperpro and other optical measuring instruments.
13. Oxygen titration system
14. Plankton nets and towing lines
15. Desktop and laptop personal computers
16. Assorted tools
17. All required sampling bottles
18. Deck incubation system
19. Pertinent MSDS

5.2 We will need the use of the following ship's equipment:

1. A-frame
2. A-frame block assembly
3. Trawl winch with conducting wire for CTD
4. Electric power for winches (440 VAC, 3 phase, 60 Amp breaker) and vans (208 VAC single phase at 60 amps for labvan, 110 VAC 10 amps for equipment van)
5. Radio direction finder
6. Space on the main deck for one equipment van
7. Space on upper deck for one laboratory van
8. Space on upper deck for incubator
9. Hand-held VHF transceivers
10. Precision depth recorder
11. Shackles, sheaves, hooks and lines
12. Shipboard Acoustic Doppler Current Profiler
13. Thermosalinograph, $p\text{CO}_2$ system, and Fluorometer
14. Meteorological suite
15. Copy machine
16. Grappling hooks and line
17. Laptop with Nobeltec charting software and GPS feed
18. Running fresh water and seawater hoses

19. Electronic mail system
20. GPS system
21. Uncontaminated seawater supply
22. Small capstan (~ 10 m/min)
23. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer, $p\text{CO}_2$ and access to real-time data through the network.
24. OTG's 24-place rosette, and 24 12-l water sampling bottles (to be used as spare)
25. 1000 lb weight.
26. Large Sea-Mac winch (Mod. 1025 EHS). 60 Amp Hubbel plug/connector (440 VAC, 3 phase, 60 Amp breaker)
27. Seapoint fluorometer (to be used as a spare)
28. Lifting basket to transport carboys from the main deck to the 02 deck
29. CTD sled and pallet jack.
30. Table at CTD sampling area.

Cast	Samples	#Bottles
<u>Kahe Pt.</u>		
s1c1 1000 m	O ₂ , Temp, DIC/Alk, Nuts, Chl a, LLN, LLPO ₄ , DOC, FCM, Salts	24
<u>Station ALOHA</u>		
s2c1 200 m	CMORE(5@25,5@45,5@75)	15
s2c2 200 m	Gas Array(2@5,25,45,75,100,125), Salts	12
s2c3 4740 m (PO-1)	O ₂ , Temp, DOC, DIC/Alk, Nuts, Salts	24
s2c4 1000 m (PO-2)	O ₂ , Temp, Nuts, DIC/Alk, DOC, Salts	24
s2c5 1000 m	PC/PN, Salts	14
s2c6 1000 m	PPO ₄ , Salts,	14
s2c7 1000 m (BEACH)	O ₂ , Temp, DIC/Alk, Nuts, LLN, LLP,DOC, Keeling, Quay, Salts	23
s2c8 1000 m	PUR, CMORE(5@1000,5@770,5@500), Salts	24
s2c9 1000 m	Primary Production, Salts	22
s2c10 1000 m	CMORE(5@125,5@200), PO(6@1000), Salts	17
s2c11 1000 m	PSi, MC(5,25,45,75,100,125,150,175), Salts	18
s2c12 1000 m	MIT, SG(6@45), Salts	16
s2c13 1000 m	ATP, MC(200,300,500,770, 1000), Salts SW(1@200,300,400,500, 600,700,800,900,1000)	24
s2c14 1000 m	PE, MC(5,25,45,75,100,125,150,175), SW(pb MC), Salts	22
s2c15 1000 m	HPLC, Chl a, Slides, Salts	22
s2c16 1000 m	Oxygen, Salts	5
<u>WHOTS Mooring</u>		
S50c1 200 m yo-yo		--

MC=Matt Church, SW=Sam Wilson, SG=Scott Grant

Ship: R/V KILO MOANA

HOT 229

Date: January 27 – 30, 2011

TIME	Thu. 1/27	Fri. 1/28	Sat. 1/29	Sun. 1/30
0000		S2C1		Transit St. 50
0100		S2C2 Gas	Net Tow	S50C1 WHOTS
0200		ACS/AC9/FRRF	S2C9 PP	Transit sed traps
0300		Deploy Gas Array	Transit gas array	Recover sed traps
0400		S2C3 PO-1	Recover gas array	Transit Honolulu
0500			S2C10 Open	
0600			Deploy PP array	
0700				
0800			S2C11 PSi	
0900	Depart Snug			
1000		Net Tow	Net Tow	
1100	Arrive Kahe (11:30) Weight cast	S2C4 PO-2 (Begin 36 hr)	S2C12 MIT	
1200	Hyperpro	Net Tow	Hyperpro ACS/AC9/FRRF	
1300	S1C1	ATE		
1400		S2C5 PC/PN	S2C13 ATP	Arrive "H" Buoy
1500	Transit ALOHA			Arrive Snug
1600				
1700		S2C6 PPO4	S2C14 PE	
1800			Recover PP array	
1900				
2000		S2C7 BEACH	S2C15 HPLC	
2100				
2200		Net Tow	Net Tow	
2300	Arrive ALOHA Deploy sed traps	S2C8 PUR	S2C16 Open (end 36 hours)	

January 29th: Sunrise 0710, Sunset 1820

6.0 HOT-229 Watch Schedule

0300-1500

Adriana Harlan – *Water Boss*

Dan Sadler

Lance Fujieki – *Tag*

Cameron Fumar – *Console*

Jefrey Snyder – *Watch Leader -Tag*

1500-0300

Susan Curless – *Watch Leader - Water Boss*

Brett Updyke – *Tag*

Bo Keopaseut – *Console*

Craig Nosse – *Chief Scientist - Tag*

At Large

Blake Watkins

Donn Viviani – *Alt Tag*

Scott Grant – *Alt Tag*

OTG

Dan Fitzgerald

Vic Polidoro