Hawaii Ocean Time-series HOT-248 Cruise Plan

Cruise ID: KM 12-27 Vessel: R/V *Kilo Moana*, University of Hawaii Master of the Vessel: Captain Gray Drewry Chief Scientist: Fernando Santiago-Mandujano, University of Hawaii OTG Marine Technicians: Trevor Goodman, Trevor Young, Jeff Koch, Jennie Mowatt

Kilo Moana phone number: 842-9817, cell # 864-0065, satellite # 011-870-773-234-249 Marine Center phone number: 842-9813

Loading: December 1, 2012@1000 Departure: December 2, 2012 @0900 (Science personnel on board by 0800). Arrival: December 6, 2012 @ 0800

1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Four stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at 21° 20.6'N, 158° 16.4'W and will be occupied on December 2nd for about 2 hours.
- 2) Station 2, referred to as Station ALOHA, is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied during on December 3rd to 5th.
- 3) Station 50, the site of WHOTS-9 Mooring (anchor position 22° 46.071'N 157° 53.956'W) will be occupied on December 5th for about one hour.
- 4) Station 6, referred to as Station Kaena, is located off Kaena Point at 21° 50.8'N, 158° 21.8'W and will be occupied on December 5th for about 2 hours.

** Operational Hazard ** The HOT Profiler Mooring (HPM) has been deployed at 22° 44.0'N, 158° 01.58'W (target location). This area of Station ALOHA (1 km radius of the target location) should be avoided at all times and free-drifting arrays must be recovered if near this area. The mooring has a small yellow buoy attached to it with a green cable. The watch circle of the buoy is estimated to be 200 meters.

1.1 SCIENTIFIC OPERATIONS

<u>Station</u>	Activities		
Kahe (sta. 1)	Weight Cast, Hyperpro cast, CTD cast (1000 m)		
ALOHA (sta. 2)	Sediment traps, gas array, net tows, CTD operations, primary		
	productivity measurements, ACS/AC9/FRRf, misc. experiments.		
WHOTS mooring station	One CTD cast (yo-yo to 200 m), surface instrument		
(Sta. 50)	intercomparisons.		
Kaena (sta. 6)	One CTD cast (near bottom)		
Underway/continuous	ADCP, thermosalinograph, pCO2 system, fluorometry, and		
	meteorology.		

Participant	Title	Affiliation/HOT Group
Susan Curless	Research Associate	UH/BEACH
Dan Sadler	Research Associate	UH/BEACH
Brett Updyke	Research Associate	UH/BEACH
Lance Fujieki	Research Associate	UH/BEACH
Shimi Rii	Graduate Student	UH/BEACH
Christopher Schvarcz	Graduate Student	UH/CMORE
Blake Watkins	Marine Engineer	UH/BEACH
Daniela Böttjer	Postdoctoral Researcher	UH/CMORE
Benedetto Barone	Postdoctoral Researcher	UH/CMORE
Sam Wilson	Postdoctoral Researcher	UH/CMORE
Jefrey Snyder	Marine Technician	UH/PO
Fernando Santiago-Mandujano	Research Associate	UH/PO
Cameron Fumar	Research Associate	UH/PO
Joseph Gum	Research Associate	UH/PO
Daniel McCoy	Data Assistant	UH/PO
James Berles	Volunteer	UH-WCC/PO
Ken Doggett	Research Associate	UH/CMORE
Ger Van den Engh	Scientist	B/D BioSciences/CMORE
Robert Bidigare	Scientist	UH
John Bullister	Scientist	NOAA/PMEL
Dave Wisegarver	Technician	NOAA/PMEL
Trevor Goodman	Marine Technician	OTG
Trevor Young	Marine Technician	OTG
Jennie Mowatt	Marine Technician	OTG
Jeff Koch	Marine Technician	OTG

3.0. SUMMARY SCHEDULE

26 November	Pre-cruise planning meeting 1330 hrs.		
1 December	Ship loading at 1000 hrs.		
2 December	Depart from Snug harbor at 0900 hrs. Science personnel on		
	board by 0800.		
2 December	Station 1 Kahe Pt. operations.		
3-5 December	Station ALOHA operations. Station 50 CTD yo-yo cast, Station		
	Kaena		
6 December	Arrive back to Snug Harbor. Full offload		

4.0. OPERATIONAL PLANS

4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 1000 lb. weight-test cast, one CTD cast to 1000 m, and a Hyperpro cast (Sect. 4.2.7) will be conducted at this location on December 2^{nd} . The A-frame, CTD crane and CTD winch will be required for these operations.

4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the sediment traps will be deployed. After the sediment trap deployment is complete, one 1000-m CTD cast will be conducted before deploying the Primary Productivity array (Sect. 4.2.3). These operations will be followed by a near-bottom CTD cast.

4.2.2. Sediment trap array deployment

Upon arrival to Station ALOHA, the floating sediment traps will be deployed at a location within Station ALOHA circle determined by forecasted current conditions and real-time ADCP data (if available). The array will be deployed from the stern, using the A-frame and Sea-Mac winch. Power requirement for the winch is 440 VAC, three phase at 10 amps. After deployment we request that the Bridge verify that the radio transmitters are functioning and directionally correct.

The array will drift for about 53 hours before recovery. The array is equipped with 2 ARGOS satellite transmitters (platform #'s 01833, 60481), 2 strobe lights, and 2 radio transmitters (channel 72, 156.625 MHz). Daily positions of the array shall be transmitted by email directly to the ship (argosfix@km.soest.hawaii.edu, password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the Bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery.

After deployment of the sediment trap array, the ship shall continue with CTD cast operations to prepare water for the Primary Productivity Array and other experiments.

4.2.3 Primary Production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (sunrise 0658 hrs on December 3rd), a free drifting incubation array will be deployed from the stern. We request the use of the A-frame for this operation and will also use the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 3028, 60482 emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), strobe lights and a radio transmitter (156.425 MHz). The **ship shall keep within site of the array** while performing CTD operations for the last 6 hours of the approximately 12-hour time the array will be in the water unless the array drifts outside of the ALOHA circle. If the array drifts out of the circle, the ship should return inside the circle to conduct CTD casts, and the monitoring of the array will be coordinated with the watch leader. The array will be recovered just at sunset (1747 hrs). CTD operations shall continue after recovery.

All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material.

4.2.4. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter Bullister sampling bottles. We will need the ship's CTD 0.680 trawl winch and A-frame for these operations. Water samples for biogeochemical measurements will be collected on each CTD cast. The cast after the deployment of the Primary Productivity Array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made every 3 hours for a 36-hour period. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0), down current, but not near drifting arrays. To avoid disruptions in the schedule, this operation should be coordinated with the chief scientist or the watch leaders (Cameron Fumar, Brett Updyke).

4.2.5. Gas Array deployment

A second free drifting incubation array will be deployed on December 4th at Station ALOHA. Samples for the gas array will be collected from Station 2 CTD cast 8. We request the use of the Aframe for this operation and will also use the Sea-Mac winch. The array is equipped with two ARGOS satellite transmitters (platform #'s 03028, 60482 emailing positions to argosfix@km.soest.hawaii.edu, password: argosfix), a strobe light and a radio transmitter (156.425 MHz). The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 25 hours after its deployment. Assistance from the Bridge is requested in plotting the drift track of the array.

4.2.6. Zoo net tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled around noon and midnight on December 3^{rd} and 4^{th} (see schedule) for a total of six slots. The A-frame and capstan will be needed for this operation. B. Watkins will be in charge of these operations.

4.2.7. Hyperpro

The Hyperpro is a profiling unit with one up-looking and one down-looking hyperspectral radiometer, a WET Labs ECO-BB2F triplet (measuring Chlorophyll-a fluorescence and backscattering in the blue and red wavelengths), temperature and conductivity sensors. This instrument also incorporates a ship mounted surface radiometer. Around noon on December 2nd, 3rd, and 5th, the Hyperpro will be deployed from the stern through a small block hung from the A-frame. The instrument is hand-lowered and retrieved with assistance from the winch.

4.2.8. ACS/AC9/FRRf/LISST

An optical package including a Wet Labs AC9 that measures water column spectral absorption and attenuation at nine wavelengths, a Chelsea Fast Repetition Rate Fluorometer (FRRf), a SeaBird Seacat with temperature, conductivity, fluorometer, and pressure sensors, and a LISST particle size and distribution analyzer will be deployed two times during the cruise.

Each deployment will consist of two up and two down profiles to a target depth of 200 m at a constant speed of 10 m/min during both the downcast and upcast. An instrument soaking period at just below the surface will be required between the two profiles. The A-frame and capstan will be needed for this operation.

4.2.9. Automated Trace Element Sampler (ATE)

On December 3rd, the ATE will be hand deployed off the back deck to a depth of 10 m to collect a trace-metal free sample. The ATE will be recovered after 30 minutes in the water. The ATE is approximately 1' tall and 4'' in diameter, weighting 5 lbs.

If the ship has been stationary at ALOHA for previous cruise activities, it is requested that the ship steams approximately 10-15 minutes up current from current position prior to each ATE deployment to limit contamination of the trace metal sample from the ship's hull.

4.2.10 HOT Profiler Mooring (HPM) communication/download

The HPM communicates at 15 minutes past every even UTC hour of the day. A transducer will be deployed off the stern for communication with the HPM. The A-frame and small capstan will be needed for this operation. This operation is scheduled for the evening of December 4th and will be coordinated with the OTG techs and J. Snyder for execution. This work should be conducted about one kilometer away from the target location of the HPM (target location: 22° 44.0'N, 158° 1.58'W)

4.2.11 Repeta pump operation

Seawater samples will be collected at 5 m intervals in the upper mixed layer using Dan Repeta's in situ pumping system at Station ALOHA during one-hour sessions at 1300 on December 3rd, 4th and 5th. The system is a small deck diaphragm pump, and the tubing is attached to a hydrowire via tape and cable ties off the fantail. R. Bidigare will be in charge of this operation.

4.3 Floating gas array and sediment trap recovery

In the early morning of December 5th, we shall transit for the recovery of the Gas Array. The Aframe and the Sea-Mac winch will be needed to retrieve the Gas Array. After the array is recovered, the ship shall transit to recover the floating sediment trap array. After the array is recovered, the ship shall transit to Station ALOHA to conduct AC9/FRRF and Hyperpro casts. After these operations are completed the ship shall transit to Station 50 and conduct one 200 m yo-yo cast.

4.4 Station 50 - WHOTS-9 Mooring

The anchor position of the WHOTS-9 mooring is 22° 46.071'N 157° 53.956'W. The watch circle of the buoy is about 2 nautical miles. Generally, the buoy stays on the edge of the watch circle. The buoy has a radar reflector that should be seen on radar. It should be detectable even in rough seas with some effort.

4.4.1 CTD yo-yo cast (subsurface instrument intercomparison)

One 200-m CTD yo-yo cast with at least 5 full cycles will be conducted near the WHOTS mooring on December 5th for subsurface instrument intercomparison. This cast should be conducted downwind/down current, and about 200 m from the mooring.

4.4.2 Surface instrument intercomparison

While on station, the ship's meteorological system shall be in operation for surface instrument intercomparisons with the WHOTS mooring.

Once the yo-yo cast is completed, the ship shall transit to Station ALOHA to conduct one AC9/FRRf cast, and one Hyperpro cast. If the mooring is positioned such that it is within the Station ALOHA circle, these operations can be performed as close to the WHOTS mooring as safely possible to extend the surface instrument intercomparison.

4.5 Station Kaena (21° 50.8'N, 158° 21.8'W)

A near-bottom CTD cast (~2500 m) will be conducted at this location in the evening of December 5^{th} . Once the CTD cast is complete, the ship shall return to Snug Harbor.

4.6 Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profiler (ADCP) will be in operation during the duration of the cruise. The OTG electronics technicians will be in charge of the ADCP system.

4.7 Thermosalinograph, pCO_2 system, Fluorometer, and meteorological system

The ship's thermosalinograph, pCO_2 system and fluorometer sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Snug Harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The ship's meteorological system shall be in operation throughout the cruise. Access to real-time underway data through the ship's network will be required. The OTG technicians will be in charge of the thermosalinograph, pCO_2 system, Fluorometer, and meteorological suite operations.

5.0 EQUIPMENT

5.1 The HOT science party shall be bringing the following

- 1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
- 2. Rosette and 24 12L Bullister sampling bottles, and all associated spare parts
- 3. One 20 ft. laboratory van with assorted equipment for radioisotope and general use (Van #23)

- 4. One 12 ft. equipment van ("Blue" Van)
- 5. Distilled, deionized water and all required chemicals and isotopes
- 6. Large vacuum waste container
- 7. Liquid nitrogen dewar
- 8. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights
- 9. Kevlar line, polypropylene line
- 10. Sediment traps and crosses
- 11. Drifting primary production array and gas array with light and radio transmitter, floats, weights, polypro. line, spare buoy, etc.
- 12. Hyperpro and other optical measuring instruments.
- 13. Oxygen titration system
- 14. Plankton nets and towing lines
- 15. Desktop and laptop personal computers
- 16. Assorted tools
- 17. All required sampling bottles
- 18. Deck incubation system
- 19. Pertinent MSDS
- 20. Chest refrigerator incubator chamber (to be located in Staging Bay)
- 21. Flow Cytometer van
- 22. John Bullister's UW van
- 23. Repeta's pump system
- 5.2 We will need the use of the following ship's equipment:
 - 1. A-frame
 - 2. A-frame block assembly
 - 3. 0.680 trawl winch with conducting wire for CTD
 - 4. Electric power for winches (440 VAC, 3 phase, 60 Amp breaker) and vans (208 VAC single phase at 60 amps for lab van, 110 VAC 10 amps for equipment van)
 - 5. Radio direction finder
 - 6. Space on the main deck for one equipment van
 - 7. Space on upper deck for two laboratory vans
 - 8. Space on upper deck for incubators
 - 9. Hand-held VHF transceivers
 - 10. Precision depth recorder
 - 11. Shackles, sheaves, hooks and lines
 - 12. Shipboard Acoustic Doppler Current Profiler
 - 13. Thermosalinograph, pCO2 system, and Fluorometer
 - 14. Meteorological suite
 - 15. Copy machine
 - 16. Grappling hooks and line
 - 17. Laptop with Nobeltec charting software and GPS feed
 - 18. Running fresh water and seawater hoses
 - 19. Electronic mail system
 - 20. GPS system
 - 21. Uncontaminated seawater supply
 - 22. Small capstan (~ 10 m/min)
 - 23. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer, pCO2 and access to real-time data through the network.
 - 24. OTG's 24-place rosette, and 24 12L water sampling bottles (to be used as spare)
 - 25. 1000 lb weight.

26. Large Sea-Mac winch (Mod. 1025 EHS). 60 Amp Hubbel plug/connector (440 VAC, 3 phase, 60 Amp breaker)

Cast		Samples	
Kahe	1000 m	O ₂ , Temp, DIC/Alk, Nuts, Chl a, LLN, LLP, DOC, FCM, JB(pb test samples*), Salts	24
	<u>n ALOHA</u>		
s2c1	1000 m	Primary Production, DV(pb PP depths), Salts, SR(pb PP depths)	22
s2c2	4740 m (PO-1)	O ₂ , Temp, DOC, DIC/Alk, Nuts, JB(pb all depths*), Salts	24
s2c3	1000 m (PO-2)	O ₂ , Temp, DOC, DIC/Alk, Nuts, JB(pb all depths*), Salts	24
s2c4	1000 m	PC/PN, SR(1@5,25,45,75,100,125,150,175), Salts	22
s2c5	1000 m	PPO4, SW(5@25,5@150), Salts	24
s2c6	1000 m (BEACH)	O ₂ , Temp, DIC/Alk, Nuts, LLN, LLP, DOC, Keeling, Quay, JB(pb Keeling/Quay depths*), MSN(pb@all depths), Salts	23
s2c7	1000 m	PUR, Salts	10
s2c8	1000 m	Gas Array, DB(3@5,45,75,100,125,6@25), Salts	23
s2c9	1000 m	AP(6@5), Salts	9
s2c10	1000 m	PSi, MC(1@5,25,45,75,100,125,150,175), SW(2@25),Salts	20
s2c11	1000 m	SR(1@5,25,45,75,100,125,150,175), Salts, CS(pb@SR depths)	10
s2c12	1000 m	ATP, MC(1@200,300,500,770), SW(1@200,300,400,500, 600,800,900,1000, 2@700), Salt	24
s2c13	1000 m	MC(1@5,25,45,75,100,125,150,175), SW(pb MC), Salts	10
s2c14	1000 m	HPLC, Chl a, Slides, Salts	22
s2c15	4740 m (PO-3)	Oxygen, MC(1@1000,2000,3000,4000), SC(2@4000) , DdV(1@300), JB(pb all depths*), ER(1@4000), Salts	16
<u>WHO</u> s50c1	TS Mooring 200 m yo-yo	SR(11@25), DdV(13@25)	24
<u>Kaena</u> s6c1	2400 m	Chl, Salts	13

(*) JB to take CFC and SF6 samples first

MC=Matt Church, SW=Sam Wilson, DV=Donn Viviani, AP=Adina Paytan, SR=Shimi Rii, CS=Chris Shvarcz, MSN=Mariona Segura-Noguera, SC=Susan Curless, DB=Daniela Böttjer, JB=John Bullister, DdV= Daniela del Valle, ER=Ethan Roth Ship: R/V *KILO MOANA* HOT 248

HOT 248 Dates: December 2 – 6, 2012

TIME	Sun. 12/2	Mon. 12/3	Tue. 12/4	Wed. 12/5	Thu. 12/6
0000			Net Tow		
0100					
0200		S2C1 PP	S2C8 Gas		
0300				AC9/FRRF	
0400		Deploy PP Array	Deploy Gas Array		
0500		S2C2 PO-1	S2C9 Open	Transit gas array	
0600				Recover array Transit sed traps	
0700				Recover sed traps	
0800			S2C10 PSi	Transit ALOHA	Arrive Snug
0900	Depart Snug				
1000		Net Tow ATE	Net Tow	AC9/FRRF	
1100	Arrive Kahe (11:30) Weight cast	S2C3 PO-2 (Begin 36 hr)	S2C11 Open		
1200	Hyperpro	Hyperpro	Net Tow	Hyperpro	
1300	S1C1 Kahe	Repeta pump	Repeta pump	Repeta pump	
1400		S2C4 PC/PN	S2C12 ATP	Transit Sta 50 S50C1 WHOTS	
1500	Transit ALOHA			Transit St. Kaena	
1600		S2C5 PPO4	HPM Comms.		
1700			S2C13 Open		
1800		Recover PP array			
1900					
2000		S2C6 BEACH	S2C14 HPLC		
2100				S6C1 Kaena	
2200		Net Tow	Net Tow		
2300	Arrive ALOHA Deploy sed traps	S2C7 PUR	S2C15 PO-3 (end 36 hours)	Transit Snug	

December 3rd: Sunrise 0658, Sunset 1747

6.0 HOT-248 Watch Schedule

0300-1500

Lance Fujieki – *Water Boss* Dan Sadler – *Alt. Tag* Jefrey Snyder– *Tag* Cameron Fumar – Watch Leader – *Console* Daniel McCoy – *Tag*

1500-0300

Susan Curless –*Water Boss* Brett Updyke – Watch Leader – *Tag* Fernando Santiago-Mandujano – Chief Scientist – *Alt. Tag* Joseph Gum – *Console* James Berles – *Tag*

0900-2100 Christopher Schvarcz

At Large

Blake Watkins Benedetto Barone Daniela Böttjer Shimi Rii Sam Wilson Ken Doggett Ger Van den Engh Robert Bidigare John Bullister Dave Wisegarver

OTG

Trevor Goodman Trevor Young Jennie Mowatt Jeff Koch