## Hawaii Ocean Time-series HOT-314 Cruise Plan

Cruise ID: KM 19-15

Vessel: R/V *Kilo Moana*, University of Hawaii Master of the Vessel: Captain David Martin

Chief Scientist: Tara M. Clemente, University of Hawaii Marine Technicians: Trevor Young and Julianna Diehl

Marine Center phone number: (808) 956-0688, Ross Barnes (808) 956-0689

KM phone numbers (in port): 808-587-8566 / 67

KM cell phone: 808-864-0065

*KM sat phone (voice): 011-870-773-234249 KM sat phone (fax): 011-870-783-207825* 

#### Tara M. Clemente Cell Number: (808) 389-0544

Pre-Cruise Meeting: July 24, 2019 at 1330 in the Moore Conference Center, C-MORE Hale.

Loading: July 31, 2019 at 0900, Pier 35.

Departure: August 1, 2019 at 0900 (Science personnel on board by 0800).

Arrival: August 5, 2019 at 1200

Post-Cruise: August 5, 2019 at 1300 in KM Conference Room

#### 1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Four stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at  $21^{\circ}$  20.6'N,  $158^{\circ}$  16.4'W and will be occupied on August  $1^{\text{st}}$  for about 3-4 hours.
- 2) Station 2, referred to as Station ALOHA, is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied August 2<sup>nd</sup> August 4<sup>th</sup>.
- 3) Station 50, the site of WHOTS-15 Mooring (anchor position 22° 46.045'N 157° 53.888'W) will be occupied for about 3-4 hours on August 4<sup>th</sup>.
- 4) ROV *Lu'ukai*, (Latitude, Longitude?). An elevator will be deployed in the vicinity of ROV *Lu'ukai* on August 4<sup>th</sup>, once operations at Station 50 are completed.
- 5) Station 6, referred to as Station Kaena, is located off Kaena Point at 21° 50.8'N, 158° 21.8'W and will be occupied on August 4<sup>th</sup> for about 2 hours.

#### 1.1 SCIENTIFIC OPERATIONS

Station Activities

Kahe (Sta. 1) Weight Cast, Hyperpro cast, CTD cast (1000 m)

ALOHA (Sta. 2) Sediment traps, Gas array, Wirewalker, Net tows, CTD operations,

Primary productivity measurements, Optics casts, Misc. experiments.

WHOTS mooring station One CTD cast (yo-yo to 200 m), surface instrument

(Sta. 50) intercomparisons.

ROV Luʻukai Deploy elevator in vicinity of ROV Lu'ukai. Kaena (Sta. 6) One near-bottom CTD cast (~ 2400 m)

Underway/continuous ADCP, thermosalinograph, fluorometry, meteorology, SeaFlow, C-Star,

Imaging FlowCytobot (IFCB)

#### 2.0. SCIENCE PERSONNEL

Participant	Title	Affiliation	Citizenship
Benedetto Barone	Scientist	UH	Italy
Brandon Brenes	Undergraduate Student	UH	USA
Karin Björkman	Scientist	UH	Sweden
Macarena Burgos	Scientist	UH	Spain
Tim Burrell	Research Associate	UH/SCOPE	New Zealand
Mathieu Caffin	Scientist	UH	France
Maximilian Cremer	Marine Technician	OTG/ROV	USA
Tara Clemente – Chief Scientist	Research Associate	UH/SCOPE	USA
Jacquelyn Corpus	Volunteer	UH	USA
Julianna Diehl	Marine Technician	OTG	USA
Blue Eisen	Marine Engineer	UH/ROV	USA
Dan Fitzgerald	Research Associate	UH	USA
Carolina Funkey	Research Associate	UH	USA
Eric Grabowski	Research Associate	UH	USA
Isaiah Kela-Pacheco	Volunteer	UH	USA
Rachel Kelly	Graduate Student	USC/SCOPE	USA
Kelsey Maloney	Student Assistant	UH	USA
Daniel Muratore	Graduate Student	GA Tech/SCOPE	USA
Tully Rohrer	Research Associate	UH/SCOPE	USA
Fernando Santiago-Mandujano	Research Associate	UH	USA
Eric Shimabukuro	Graduate Student	UH	USA
Ryan Tabata	Research Associate	UH/SCOPE	USA
Kristin Thompson	Graduate Student	UH	USA
Tracy Villareal	Scientist	UT Austin	USA
Blake Watkins	Marine Engineer	UH	USA
Trevor Young	Marine Technician	OTG	USA
Jinchun Yuan	Scientist	ECSU	USA
Lauren Yumol	Graduate Student	UH	USA

#### 3.0. SUMMARY SCHEDULE

24 July	Pre-cruise planning meeting 1330 hrs, Moore Conference Center, C-MORE Hale.
31 July	Equipment loading at 0900 hrs, Pier 35.
1 August	Depart from Pier 35 at 0900 hrs. Science personnel on-board by 0800.
1 August	Station 1 Kahe Pt. operations.
2-4 August	Station 2 ALOHA operations, Station 50 CTD yo-yo cast, ROV Lu'ukai
	operations.
5 August	Station 6 CTD cast.
5 August	Arrive back to Pier 35 at 1200hrs.

5 August 5 August Post-cruise meeting at 1300 hrs. KM Conference Room.

#### 4.0. OPERATIONAL PLANS

#### 4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 1300 lb. weight-test cast to 500 m, a Hyperpro cast (Sect. 4.2.9), one CTD cast to 1000 m (4.2.5) and one aerial drone operation (4.8) will be conducted at this location on August 1<sup>st</sup>. The ships A-frame and Dynacon winch will be needed for these operations. After the operations are satisfactorily completed, the ship shall proceed to Station ALOHA.

#### 4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the Wirewalker will be deployed (Sect. 4.2.2). Once the Wirewalker is deployed, the Sediment Traps will be deployed (Sect. 4.2.3). After these operations are completed, one 1000-m cast will be conducted to collect water for the Primary Production Array. Following this, the Trace Metal Pump (4.2.12) will be deployed to collect water. Once pumping operations are completed the Primary Production array will be deployed (4.2.4). These operations will be followed by a near-bottom CTD cast and the start of the 36-hour water column observations at Station ALOHA.

# NOTE: Array tracking is facilitated through the SOEST Cruise and Drifter Tracks tool found at <a href="http://hahana.soest.hawaii.edu/nowcast/loctable.html">http://hahana.soest.hawaii.edu/nowcast/loctable.html</a>

#### 4.2.2 Wirewalker deployment

Upon arrival to Station ALOHA a Wirewalker (Del Mar Oceanographic) will be deployed to take hydrographic and optical observations in the upper 400 m of the water column. The instrument is approximately 1.5 m long and 0.6 m wide and weighs approximately 30 Kg. The instrument will be deployed on a wire with a 40 Kg bottom weight and a surface buoy with strobe light and Pacific Gyre positioning system (ID: DMO-GLBCN-0003 or DMO-GLBCN-0004), Xeos 51020, Iridium (platform #: 704320).

The Wirewalker will be deployed at a location within Station ALOHA, to be determined by observed local and forecasted currents to avoid possible entanglement with the WHOTS mooring. The instrument will stay in the water for approximately 56 hours. Deployment and recovery will be conducted from the back deck through the A-frame and using the SeaMac winch, each operation will take 30 to 60 min. Two ABs will be required to operate the A-frame and winch respectively. Blake Watkins will be in charge of this deployment.

After deployment of the Wirewalker, the ship shall prepare to deploy the sediment trap array.

#### 4.2.3. Sediment trap array deployment

The floating sediment traps will be deployed in close proximity to the Wirewalker, so the two arrays drift in a similar direction. The array will be deployed from the back of the deck thru the A-frame and using the SeaMac winch. After deployment we request that the bridge verify that the radio transmitters are functioning and directionally correct. The Sediment Trap array will consist of one cross with 12 particle interceptor traps (PIT) at 150m.

The array will drift for about 56 hours before recovery. The array is equipped with 1 ARGOS satellite transmitter (platform #: 85857), 1 Novatech Iridium beacon (platform #: 59100), strobe lights, a radio transmitter (channel 72: 156.625 MHz). Daily positions of the array shall be transmitted by email directly to the ship (argosfix@km.soest.hawaii.edu), password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery. Blake Watkins will be in charge of this deployment.

After deployment of the sediment trap array, one 1000 m CTD cast and the trace metal pumping operation shall be conducted. Following these operations, the ship shall prepare to deploy the Primary Productivity Array.

#### 4.2.4 Primary production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (Sunrise 0604 hrs on August 2<sup>nd</sup>), a free drifting incubation array will be deployed from the back of the deck thru the A-frame and using the SeaMac winch. The primary production incubation array will be deployed at a location within Station ALOHA, to be determined by observed local and forecasted currents to avoid possible entanglement with the WHOTS mooring. The array is equipped with ARGOS satellite transmitter (platform # 60484), Xeos 50030, strobe lights and a radio transmitter (channel 74: 156.725 MHz). Positions of the array will be emailed to <a href="mailto:argosfix@km.soest.hawaii.edu">argosfix@km.soest.hawaii.edu</a>, password: argosfix. The ship shall keep within site of the array while performing CTD operations for the last 6 hours of the approximately12-hour time the array will be in the water unless the array drifts outside of the ALOHA circle. If the array drifts out of the circle, the ship should return inside the circle to conduct CTD casts, and the monitoring of the array will be coordinated with the watch leader. The array will be recovered just at sunset (1913 hrs). CTD operations shall continue after recovery. All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material. Blake Watkins will be in charge of this deployment.

After deployment of the Primary Production Array, the ship shall transit to the center of the station circle to conduct a bottom CTD cast, S2C2 (approximately 4740 m).

#### 4.2.5. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter Bullister sampling bottles. We will need the ship's CTD winch and A-frame for these operations. Water samples for biogeochemical measurements will be collected on each cast. The cast after the deployment of the Primary Productivity Array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made continuously every 3 hours for a 36-hour period, ending with a second near-bottom cast. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0). To avoid disruptions in the schedule, this operation should be coordinated with the chief scientist or the watch leaders (Carolina Funkey and Tully Rohrer).

#### 4.2.6 Lowered Acoustic Doppler Current Profiler

The HOT rosette configuration includes a Teledyne Workhorse Mariner Model 600 kHz lowered-ADCP (LADCP) for current measurements on down- and up-cast. The LADCP, operating in single ping mode, will record measurements internally at a rate of 4 Hz. These measurements will then be downloaded after each cast via an RS232-to-ethernet connection. This will require direct connection to the ADCP after each cast, with data download before the next cast.

#### 4.2.7 Continuous Particle Imaging and Classification System (CPICS)

A CPICS system will be attached to the HOT rosette frame to collect imagery data on every 1000m cast. The CPICS system is rated to 1000m and will need to be removed from the rosette frame for casts going deeper. The system is self contained and the data will be transferred after each CTD cast. The battery will need to recharged on occasion.

#### 4.2.8. Gas Array deployment

A free drifting incubation array will be deployed the third day of the cruise at Station ALOHA. Samples for the gas array will be collected from Station 2 CTD cast 8. The gas array will be deployed from the back of

the deck thru the A-frame and using the SeaMac winch. The gas array be deployed at a location within Station ALOHA, to be determined by observed local and forecasted currents to avoid possible entanglement with the WHOTS mooring. The array is equipped with ARGOS satellite transmitter (platform # 60484), Xeos 50030, strobe lights and a radio transmitter (channel 74: 156.725 MHz). Positions of the array will be emailed to <a href="mailto:argosfix@km.soest.hawaii.edu">argosfix@km.soest.hawaii.edu</a>, password: argosfix. The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 25 hours after its deployment. Assistance from the bridge is requested in plotting the drift track of the array. B. Watkins will be in charge of this deployment.

#### 4.2.9. Hyperpro

The Hyperpro is a profiling unit with one up-looking and one down-looking hyperspectral radiometer, a WET Labs ECO-BB2F triplet (measuring Chlorophyll-*a* fluorescence and backscattering in the blue and red wavelengths), temperature and conductivity sensors. This instrument also incorporates a ship mounted surface radiometer. Around 1400 on the first, second and fourth days, the Hyperpro will be deployed from the stern through a small block hung from the A-frame. The instrument is lowered and retrieved by hand. Each deployment will consist of two profiles and one yo-yo (5 x 20m) before the instrument is retrieved.

#### 4.2.10. Optics

An optical package including a SeaBird Seacat with temperature, conductivity, and pressure sensors, a Wetlabs ECO triplet measuring g backscatter, chlorophyll fluorescence, and CDOM fluorescence and a LISST particle size and distribution analyzer will be deployed during the cruise. Each deployment will consist of three up and two down profiles to a target depth of 200 m at a constant speed of 10 m/min during both the downcast and upcast. An instrument soaking period at just below the surface will be required between the two profiles. The A-frame and capstan will be needed for this operation.

## 4.2.11. Zooplankton Net Tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled around noon and midnight on the second, third, and fourth days (see schedule) for a total of six slots. The A-frame and small capstan will be needed for this operation. B. Watkins will be in charge of these operations.

#### 4.2.12 Trace Metal Pump

A trace metal surface pump will be deployed once from the stern towards the beginning of the cruise for 30-45 minutes. The pump can be deployed off the side deck, as no A-frame needed. The pump inlet will have a 15 lb weight attached to keep it lowered in the water. The pump will require a compressed air source from the ship.

#### 4.2.13 Video Plankton Recorder (VPR)

A Video Plankton Recorder (VPR) is an underwater video microscope system that that takes images of plankton and particulate matter. The VPR will be lowered into the water from the stern. We will need the ship's CTD winch, hydrowire and A-frame for this operation. The VPR will be oscillated between the surface and 400 meters depth while being towed at a speed of 2.5 knots. The VPR will be deployed four times during the cruise for approximately 1-1.5hrs, depending on allottable time as to not delay water column CTD operations and interrupt the 36 hour burst sampling period.

#### 4.2.14 Acoustic Zooplankton Fish Profiler (AZFP)

An Acoustic Zooplankton Fish Profiler will be deployed from the stern of the ship on the third day of the cruise. Each AZFP deployment will be lowered to a depth of 500 meters at a steady rate. The AZFP will be deployed four times during the cruise for approximately 1 hr, depending on allottable time as to not delay water column CTD operations and interrupt the 36 hour burst sampling period. The A-frame and SeaMac winch will be needed for this operation.

## 4.3 Gas Array, Sediment Trap Array and Wire Walker recovery

In the morning of August 4<sup>th</sup>, after the optics cast has been completed, the ship shall transit for the recovery of the Gas Array. The A-frame and the Sea-Mac winch will be needed to retrieve the sediment trap array. After the Gas Array is recovered, the ship shall transit to recover the floating sediment trap array. On completion of sediment trap array recovery, the ship shall transit to recover the Wirewalker. Blake Watkins will be in charge of these operations. After the Wirewalker is recovered, the ship shall transit to Station 50. Upon arrival at Station 50 a Hyperpro cast, aerial drone operations, one 200 m CTD yo-yo cast and ADCP inter comparisons will be conducted. Following the ADCP inter comparisons the VPR will be deployed. Once the VPR operations are complete the ship will transit to the site of the ROV *Lu'ukai*.

#### 4.4 Station 50 - WHOTS-15 Mooring

The anchor position of the WHOTS-15 mooring is 22° 46.045'N 157° 53.888'W. The watch circle of the buoy is about 2 nautical miles. Generally, the buoy stays on the edge of the watch circle. The buoy can be detected via radar in good weather conditions but is harder to detect with larger sea states.

## 4.4.1 CTD yo-yo cast (subsurface instrument inter-comparison)

One 200-m CTD yo-yo cast with at least 5 full cycles will be conducted near the WHOTS mooring on August 4<sup>th</sup> for subsurface instrument inter-comparison. This cast should be conducted downwind, down current, and about 200 m from the mooring.

#### 4.4.2 Surface instrument inter-comparison

While on station, the ship's meteorological system shall be in operation for surface instrument Inter-comparisons with the WHOTS mooring. Once the yo-yo cast is completed, ADCP inter-comparisons will be run between the shipboard ADCP system and the moored instrument on the WHOTS-15 mooring line. These comparisons should also be conducted downwind, down current, and about 200 m from the mooring.

## 4.4.3 Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profilers (ADCP) will be in operation during the duration of the cruise. The OTG technicians will be in charge of the ADCP system. After operations at Station 50 are completed, the ship shall transit to the ROV *Lu'ukai* location

#### 4.5. ROV Lu'ukai (Latitude, Longitude?)

An elevator will be deployed in the vicinity of the ROV Lu'ukai. The plan will be to use the 3x19 cable to lower the elevator to rest near the ROV. As a backup plan the elevator will be dropped to freefall to the sea bed instead. Once operations are complete the ship shall transit to Station Kaena.

#### 4.6. Station Kaena (21° 50.8'N, 158° 21.8'W)

A near-bottom CTD cast (~2500 m) will be conducted at this location in the early morning of August 5<sup>th</sup>. Once the CTD cast is complete, the ship shall return to Pier 35.

## 4.7. Thermosalinograph, Fluorometer and pCO<sub>2</sub>

The ship's thermosalinograph, fluorometer and pCO<sub>2</sub> sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Honolulu Harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The ship's meteorological system shall be in operation throughout the cruise. Access to real-time underway data through the ship's network will be required. The OTG technicians will be in charge of the thermosalinograph, Fluorometer, and meteorological suite operations.

## 4.7.1 SeaFlow, Inline C-Star Transmissometer and Imaging FlowCytobot (IFCB)

In addition to the continuous thermosalinograph and fluorometer sampling, the SeaFlow, an inline C-Star Transmissometer, and the IFCB will sample continuously from the uncontaminated seawater supply system throughout the duration of the cruise while the ship is outside of Honolulu Harbor. Access to real-time underway data through the ships network is required. The SCOPEOps technicians and UH personnel will be in charge of these instruments and operations.

## 4.8 Aerial Drone Operations

An aerial drone equipped with chemical sensors will collect atmospheric profiles each day for about 20 minutes. Launch and recovery is requested from an open deck area determined in consultation with the captain and OTG technicians. A licensed individual will operate the drone according to all applicable regulations.

#### 5.0 EQUIPMENT

## 5.1. The HOT science party shall be bringing the following

- 1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
- 2. Rosette and 24 12L Bullister sampling bottles, and all associated spare parts
- 3. Lowered Acoustic Doppler Current Profiler (LADCP)
- 4. One 20 ft. laboratory van (#23) with assorted equipment for radioisotope and general use, and one 10 ft. blue storage van (PO) for equipment and spare storage.
- 5. Distilled, deionized water and all required chemicals and isotopes
- 6. Large vacuum waste containers
- 7. Liquid nitrogen dewars
- 8. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights, line, sediment traps and crosses.
- 9. Drifting primary production array with strobe lights, satellite and radio transmitters, floats, weights, line primary production bottles and spreader bars.
- 10. Drifting gas array with strobe lights, satellite and radio transmitters, floats, weights, line, 4 L bottles and short mounting bars.
- 11. Drifting Wirewalker array with surface buoy, strobe lights, satellite transmitters, floats, weights, 400m and cable.
- 12. Oxygen titration system
- 13. Plankton nets and towing lines
- 14. Desktop and laptop personal computers
- 15. Assorted tools
- 16. All required sampling bottles
- 17. Pertinent MSDS
- 18. Wirewalker
- 19. SeaFlow
- 20. Inline C-Star Transmissometer
- 21. Imaging FlowCytobot (IFCB)
- 22. On deck Incubators
- 23. Continuous Particle Imaging and Classification System (CPICS)
- 24. Video Plankton Recorder (VPR)
- 25. Acoustic Zooplankton Fish Profiler (AZFP)
- 26. Trace Metal Pump
- 27. Aerial Drones
- 28. Tumbler
- 29. Caron Incubator
- 30. 2-pallets worth of gear for ROV Elevator

## 5.2. We will need the use of the following ship's equipment:

- 1. A-frame
- 2. A-frame block assembly
- 3. CTD winch
- 4. Electric power
  - -440/480 VAC, 3 phase 60Hz, 60amp for winches
  - -208 VAC single phase at 60 amps for lab vans
- 5. Space on upper 01 deck port side for one 10 ft van (Blue Equipment van)
- 6. Space on upper 01 deck port side for one 20 ft van (#23)
- 7. Space on 02 deck for incubators
- 8. Space in science hold for incubator
- 9. Space on deck for ~4 deck baskets of array gear
- 10. Space on deck for VPR (3ft x 6 ft)
- 11. Small capstan (~ 10 m/min)
- 12. SeaMac Winch
- 13. Radio direction finder
- 14. Hand-held VHF transceivers
- 15. Shackles, sheaves, hooks and lines
- 16. Precision depth recorder
- 17. Shipboard Acoustic Doppler Current Profiler
- 18. Thermosalinograph, pCO<sub>2</sub> system, and Fluorometer
- 19. Meteorological suite
- 20. Grappling hooks and line
- 21. Navlink2 PC or equivalent
- 22. Running fresh water and seawater, hoses
- 23. Uncontaminated seawater supply
- 24. Source of compressed air for Trace Metal pump
- 25. -80°C Freezer
- 26. 4°C Refrigerator and -20°C Freezer
- 27. Distilled, deionized water system
- 28. Electronic mail system
- 29. GPS system
- 30. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer, SeaFlow, inline C-Star transmissometer and IFCB and access to real-time data through the network.
- 31. OTG's 24-place rosette, and 24 12-l water sampling bottles (to be used as spare)
- 32. ~1300 lb weight
- 33. Remote CTD dbar pressure display in the winch operator area.
- 34. Monitor in CTD Lab displaying ship coordinates, bottom depth and GMT.
- 35. OTG's transmissometer (preferably SN 1366)

Ship: R/V Kilo Moana HOT 314 CTD CASTS Date: August 1 - 5, 2019

	Cast	Samples	#Bottles
Kahe			1.5
s1c1	1000 m	O <sub>2</sub> , Temp, DIC/Alk, pH, Nuts, LLN, LLP, Chl a, Salts	15
Station s2c1	n ALOHA 200 m	Primary Production, Chl a, FCM, <b>SF-S</b> (pb 3@ 5, 25, 45, 75, 100, 125) and O2(1@15), Salts	24
s2c2	4740 m (PO-1)	O <sub>2</sub> , Temp, DOC, DIC/Alk, pH, Ref Si, Nuts, Salts	24
s2c3	1000 m (PO-2)	O <sub>2</sub> , Temp, DOC, DIC/Alk, pH, Nuts, Ref Si, Salts	24
s2c4	1000 m	PC/PN, DNA(1@5,25,45,75), Salts	18
s2c5	1000 m	PPO4, <b>SF-S</b> (1@5, 25) and O2(1@15),Salts	17
s2c6	1000 m (BEACH)	O <sub>2</sub> , Temp, DIC/Alk, pH, Nuts, LLN, LLP, DOC, Keeling, Quay, Salts, <b>SF-S</b> (1@5,pb@25)	24
s2c7	1000 m	<b>SF-S</b> (1@5, 25), DNA(1@,100,125,150,175), Salts <b>MCA</b> (1@5,25,45,75,100,125,150,175,250,500)	22
s2c8	1000 m	Gas Array(3@5,25,45,75,100,125), <b>SF-S</b> (1@5, 25), Salts	22
s2c9	1000 m	DNA(1@200,225,250,275), <b>SF-S</b> (1@5, 25) and O2(1@15), <b>MC</b> (1@5, 25, 45, 75, 100, 125, 150, 175), Salts	17
s2c10	1000 m	PSi, <b>SF-S</b> (1@5, 25), <b>MCA</b> (4@5,75,125),Salts	24
s2c11	1000 m	<b>SF-S</b> (1@5, 25), <b>PO</b> (6@1000), Salts	15
s2c12	1000 m	ATP, DNA(1@300,400,500,770), <b>SF-S</b> (1@5, 25), Salts	17
s2c13	1000 m	<b>SW</b> (1@5,25,45,75,100,125,150,175, 200, 300, 400, 600, 800) <b>SF-S</b> (1@5, 25) and O2(1@15),Salts	18
s2c14	1000 m	HPLC, Chl a, MCA(1@5,25,45,75,100,125)Salts	17
s2c15	4740 m (PO-3)	Oxygen, DNA(1@1000,2000,3000,4000), ML (3@1000), salts	21
<b>WHO</b> s50c1	TS Mooring 200 m yo-yo	DIC/TA(1@5), <b>SCOPE</b> (10@ 25, 200m)	21
Kaena s6c1	2400 m	Chl a, Salts	13
<u>Under</u>	way Samples	<b>DF</b> (4@ 20L)	

MC=Matt Church, SW=Sam Wilson, SF-S=Sara Ferrón-Smith, MCA=Mathieu Caffin, ML=Morgan Linney DF= Dan Fitzgerald

Ship: R/V Kilo Moana HOT 314 Date: Aug 1 – Aug 5, 2019

TIME	Thurs. 8/1	Friday. 8/2	Sat. 8/3	Sun. 8/4	Mon. 8/5
0000		Deploy WireWalker	Transit to pump tanks		
0100		Deploy Sed Trap	AZFP (500m)		S6C1 Kaena
0200		S2C1 PP	S2C8 Gas		
0300		TM Pump		Optics	
0400		Deploy PP Array	Deploy Gas Array		
0500		S2C2 PO-1(Deep)	S2C9 Open	Transit Gas Array	
0600			VPR (400m)	Recover Gas Array Transit Sed Traps	
0700			AZFP (500m)	Recover Sed Traps	
0800	All Sci. Aboard		S2C10 PSi	Transit WireWalker	
0900	Depart Pier 35		Transit to pump tanks	Recover WireWalker	
1000				Transit St. 50	
1100	Arrive Kahe(11:30) Weight Cast	S2C3 PO-2 (Begin 36 hr)	S2C11 Open	HyperPro	
1200	HyperPro	Net Tow	Net Tow Net Tow	Aerial Drone Ops	Arrive Pier 35
1300		HyperPro	Aerial Drone Ops	S50C1 WHOTS	
1400	S1C1 Kahe	S2C4 PC/PN	S2C12 ATP	ADCP Inter-comp	
1500	Aerial Drone Ops	Transit to pump tanks	VPR (400m)	VPR (400m)	
1600	Transit ALOHA	Aerial Drone Ops	AZFP (500m)	ROV – Deploy Elevator	
1700		S2C5 PPO4	S2C13 Open		
1800		Transit to PP array	Transit to pump tanks		
1900		Recover PP array			
2000		S2C6 BEACH	S2C14 HPLC		
2100		VPR (400m)	AZFP (500m)		
2200		Net Tow Net Tow	Net Tow	Transit to Kaena	
2300	Arrive ALOHA	S2C7 Open	S2C15 PO-3 (Deep) (end 36 hours)		

August 2<sup>nd</sup>: Sunrise 0604, Sunset 1913

# 6.0 HOT-314 Watch Schedule

## 0300-1500

Macarena Burgos – Alt Tag
Tara Clemente – Chief Scientist
Dan Fitzgerald – Console
Carolina Funkey – Water Boss, Watch Leader
Eric Grabowski – Tag
Isaiah Kela-Pacheco
Fernando Santiago-Mandujano – Alt Tag
Ryan Tabata – Tag
Lauren Yumol

## 1500-0300

Karin Björkman – Water Boss Brandon Brenes – Alt Tag Tim Burrell – Alt Tag Kelsey Maloney – Tag Daniel Muratore Tully Rohrer – Console, Watch Leader Eric Shimabukuro – Tag Kristin Thompson Jacquelyn Corpus

# At Large

Benedetto Barone Mathieu Caffin Maximilian Cremer Blue Eisen Rachel Kelly Tracy Villareal Blake Watkins Jinchun Yuan

## **OTG**

Trevor Young Julianna Diehl