

Hawaii Ocean Time-series HOT-325 Cruise Plan

Cruise ID: KM 20-14

Vessel: R/V *Kilo Moana*, University of Hawaii

Master of the Vessel: Captain Joey Daigle

Chief Scientist: Tully Rohrer, University of Hawaii

Marine Technicians: Trevor Young, Lance Frymire

Marine Center phone number: (808) 956-0688, Barry Choy (808) 864-0122

KM phone numbers (in port): 808-587-8566 / 67

KM cell phone: 808-864-0065

KM sat phone (voice): 011-870-773-234249

KM sat phone (fax): 011-870-783-207825

Tully Rohrer Cell Number: (970) 708-7601

Pre-Cruise Meeting: December 8th, 2020 at 1330 via Zoom

Loading: December 16th, 2020 at 0900, Pier 35.

Departure: December 17th, 2020 at 0800 (**Science personnel on board by 0700**).

Arrival: December 21st, 2020 at 0800

Post-Cruise Meeting: December 22nd, 2020 at 1330 via Zoom

1.0 SCIENTIFIC OBJECTIVES

The objective of the cruise is to maintain a collection of hydrographic and biogeochemical data at the Hawaii Ocean Time-series (HOT) stations. Four stations will be occupied during the cruise, in the following order:

- 1) Station 1, referred to as Station Kahe, is located at 21° 20.6'N, 158° 16.4'W and will be occupied on December 17th for about 3-4 hours.
- 2) Station 2, referred to as Station ALOHA, is defined as a circle with a 6 nautical mile radius centered at 22° 45'N, 158°W. This is the main HOT station and will be occupied December 18th – December 20th.
- 3) Station 52, the site of WHOTS-16 Mooring (anchor position 22° 40.01'N 157° 56.96'W) will be occupied for about 3-4 hours on December 20th.
- 4) Station 6, referred to as Station Kaena, is located off Kaena Point at 21° 50.8'N, 158° 21.8'W and will be occupied on December 20th for about 2 hours.

1.1 SCIENTIFIC OPERATIONS

Station

Kahe (Sta. 1)

ALOHA (Sta. 2)

WHOTS mooring station (Sta. 52)

Kaena (Sta. 6)

Activities

Weight Cast, Hyperpro cast, CTD cast, Trace Metal CTD (1000 m)
IRSC Traps, Sediment traps, WireWalker, Primary productivity array, Gas array, Net tows, CTD operations, Optics casts, Trace Metal CTD casts, Plankton Camera casts, Misc. experiments.

One CTD cast (yo-yo to 200 m), Hyperpro, Trace Metal CTD cast, surface instrument intercomparisons.

One near-bottom CTD cast (~ 2400 m)

Underway/continuous ADCP, thermosalinograph, fluorometry, meteorology, SeaFlow, C-Star, Imaging FlowCytobot (IFCB)

2.0. SCIENCE PERSONNEL

Participant	Title	Affiliation	Citizenship
Eleanor Bates	Graduate Student	UH	USA
Brandon Brenes	Research Assistant	UH	USA
Tim Burrell	Research Associate	UH/SCOPE	New Zealand
Dan Fitzgerald	Research Associate	UH	USA
Lance Frymire	Marine Technician	OTG	USA
Nicholas Hawco	Scientist	UH	USA
Lucie Knor	Research Assistant	UH	Germany
Fernando Pacheco	Research Associate	UH	Brazil
Tully Rohrer	Research Associate	UH/SCOPE	USA
Andrés Salazar Estrada	Graduate Student	UH	Chile
Dan Sadler	Research Associate	UH	USA
Eric Shimabukuro	Graduate Student	UH	USA
Ryan Tabata	Research Associate	UH/SCOPE	USA
Blake Watkins	Marine Engineer	UH	USA
Trevor Young	Marine Technician	OTG	USA

3.0. SUMMARY SCHEDULE

9 December	Pre-cruise planning meeting 1330 hrs, via Zoom.
16 December	Equipment loading at 0900 hrs, Pier 35.
17 December	Depart from Pier 35 at 0800 hrs. Science personnel on-board by 0700.
17 December	Station 1 Kahe Pt. operations.
18-20 December	Station 2 ALOHA operations, Station 52 CTD yo-yo cast. Station 6 CTD cast.
21 December	Arrive back to Pier 35.
22 December	Post-cruise meeting at 1330 hrs via Zoom

4.0. OPERATIONAL PLANS

4.1. Station Kahe (21°20.6'N, 158°16.4'W)

A 1300 lb. weight-test cast to 500 m, a Hyperpro cast (Sect. 4.2.9), one CTD cast to 1000 m (4.2.6), and a Trace Metal CTD cast (4.8) will be conducted at this location on December 17th. The ships A-frame, CTD winch, and SeaMac winch will be needed for these operations. After the operations are satisfactorily completed, the ship shall proceed to Station ALOHA.

4.2. Station ALOHA (22°45'N, 158°W with 6 nm radius)

4.2.1. Upon arrival to Station ALOHA, the IRSC Traps will be deployed (Sect. 4.2.2). Then, the Sediment Trap Array (Sect 4.2.3) will be deployed nearby so that it drifts in a similar fashion to the IRSC array. Then the Wirewalker will be deployed (Sect. 4.2.4). After these operations are completed, one 1000-m cast will be conducted to collect water for the Primary Production Array. Following this, the Primary Production array will be deployed (4.2.5). These operations will be followed by a near-bottom CTD cast and the start of the 36-hour water column observations at Station ALOHA.

NOTE: Array tracking is facilitated through the SOEST Cruise and Drifter Tracks tool found at <http://hahana.soest.hawaii.edu/nowcast/loctable.html>

4.2.2. IRSC Sediment trap array deployment

Upon arrival to Station ALOHA, the IRSC sediment traps will be deployed at a location to be determined by observed local and forecasted currents to avoid possible entanglement with the WHOTS mooring. The array will be deployed from the back of the deck thru the A-frame and using the SeaMac winch. After deployment we request that the bridge verify that the radio transmitters are functioning and directionally correct. The IRSC array will consist of three indented rotating sphere traps on a custom frame at 150 m with a single cross of standard HOT PIT Sediment Traps above. The array will drift for about 56 hours before recovery. The array is equipped with a satellite position transmitter, strobe lights, and a radio transmitter (See section 6.0 for transmitter IDs). Daily positions of the array shall be transmitted by email directly to the ship (argosfix@km.soest.hawaii.edu, password: argosfix), therefore the ship will **not** need to keep within site of the array until the time of the recovery. Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery. Blake Watkins will direct this deployment.

4.2.3. Sediment trap array deployment

The floating sediment traps will be deployed near the IRSC Trap array, so the two arrays drift in a similar direction. The array will be deployed from the back of the deck through the A-frame and using the SeaMac winch. After deployment we request that the bridge verify that the radio transmitters are functioning and directionally correct. The Sediment Trap array will consist of one cross with 12 particle interceptor traps (PIT) at 150m, and one cross above it with 4 traps.

The array will drift for about 56 hours before recovery. The array is equipped with 1 ARGOS satellite transmitter, 1 Novatech Iridium beacon, strobe lights, and a radio transmitter (see section 6.0 for transmitter IDs). Assistance from the bridge is requested in plotting the drift track of the array. We request the use of the ship's radio direction finder for locating the array before recovery. Blake Watkins will direct this deployment.

4.2.4. Wirewalker™ deployment

A Wirewalker (Del Mar Oceanographic) will then be deployed to take hydrographic and optical observations in the upper 400 m of the water column. The instrument is approximately 1.5 m long and 0.6 m wide and weighs approximately 30 Kg. The instrument will be deployed on a wire with a 40 Kg bottom weight and a surface buoy with strobe light and Pacific Gyre positioning system (See section 6.0 for transmitter IDs).

The Wirewalker will be deployed near to the Sediment Trap array so that the arrays drift in a similar direction. The instrument will stay in the water for approximately 56 hours. Deployment and recovery will be conducted from the back deck through the A-frame and using the SeaMac winch. Two ABs will be required to operate the A-frame and winch, respectively. Blake Watkins will direct this deployment.

After array deployments conclude, one 1000 m CTD cast shall be conducted. Following these operations, the ship shall prepare to deploy the Primary Productivity Array.

4.2.5. Primary production experiment

Samples for the primary productivity experiment will be collected from the rosette. Before dawn (Sunrise 0703 hrs on December 18th), a free drifting incubation array will be deployed from the back of the deck thru the A-frame and using the SeaMac winch. The primary production incubation array will be deployed at a location within Station ALOHA to be determined by observed local and forecasted currents to avoid possible entanglement with the WHOTS mooring. Positions of the array will be emailed to argosfix@km.soest.hawaii.edu, password: argosfix. (See section 6.0 for Trasmmitter IDs).

The array will be recovered at sunset (1754 hrs). CTD operations shall continue after recovery. All radioactive waste generated by the experiment shall be returned to the University of Hawaii. Only qualified personnel shall handle radioactive material. Blake Watkins will direct this deployment.

After deployment of the Primary Production Array, the ship shall transit to the center of the station circle to conduct a bottom CTD cast, S2C2 (approximately 4740 m).

4.2.6. Water column measurements

Vertical profiles of temperature, conductivity and dissolved oxygen will be made with an instrument package consisting of a Sea-Bird CTD attached to a 24-place rosette with 12 liter Bullister sampling bottles. We will need the ship's CTD winch and A-frame for these operations. Water samples for biogeochemical measurements will be collected on each cast. The cast after the deployment of the Primary Productivity Array shall be made to the near bottom (approximately 4740 m). Following this cast, a series of 1000-m casts shall be made continuously every three hours for a 36-hour period, ending with a second near-bottom cast. It is highly desired that this burst sampling be done without interruption and we request the ship to maintain position within the study area for that period of time, and repositioning to the center of the Station before each cast whenever possible.

Whenever pumping of the ship's tanks is needed, it must be conducted outside the circle that defines station ALOHA (Sect. 1.0). To avoid disruptions in the schedule, this operation should be coordinated with the chief scientist or the watch leaders (**Fernando Pacheco and Tully Rohrer**).

4.2.7. Lowered Acoustic Doppler Current Profiler

The HOT rosette configuration includes a Teledyne Workhorse Mariner Model 600 kHz lowered-ADCP (LADCP) for current measurements on down- and up-cast. The LADCP, operating in single ping mode, will record measurements internally at a rate of 4 Hz. These measurements will then be downloaded after each cast via an RS232-to-ethernet connection. This will require direct connection to the ADCP after each cast, with data download before the next cast.

4.2.8. Gas Array deployment

A free drifting incubation array will be deployed the third day of the cruise at Station ALOHA. Samples for the gas array will be collected from Station 2 CTD cast 8. The gas array will be deployed from the back of the deck thru the A-frame and using the SeaMac winch. The gas array will be deployed at a location within Station ALOHA to be determined by observed local and forecasted currents to avoid possible entanglement with the WHOTS mooring. The array is equipped with GPS transmitters, strobe lights and a radio transmitter (See Section 6.0 for transmitter IDs). Positions of the array will be emailed to argosfix@km.soest.hawaii.edu, password: argosfix. The ship will **not** need to keep within sight of the array until the time of the recovery, approximately 25 hours after its deployment. Assistance from the bridge is requested in plotting the drift track of the array. Blake Watkins will be in charge of this deployment.

4.2.9. Hyperpro

The Hyperpro is a profiling unit with one up-looking and one down-looking hyperspectral radiometer, a WET Labs ECO-BB2F triplet (measuring Chlorophyll-*a* fluorescence and backscattering in the blue and red wavelengths), temperature and conductivity sensors. This instrument also incorporates a ship mounted surface radiometer. Around 1400 on the first, second and fourth days, the Hyperpro will be deployed from the stern through a small block hung from the A-frame. The instrument is lowered and retrieved by hand. Each deployment will consist of two profiles and one yo-yo (5 x 20m) before the instrument is retrieved.

4.2.10. Optics

An optical package including a SeaBird Seacat with temperature, conductivity, and pressure sensors, a Wetlabs ECO triplet measuring backscatter, chlorophyll fluorescence, and CDOM fluorescence, and a LISST particle size and distribution analyzer will be deployed during the cruise. Each deployment will consist of three up and two down profiles to a target depth of 200 m at a constant speed of 10 m/min during both the downcast

and upcast. An instrument soaking period at just below the surface will be required between the two profiles. The A-frame and capstan will be needed for this operation.

4.2.11. Zooplankton Net Tows

A plankton net will be deployed from the stern and shall be towed for half-hour periods. Half-hour periods are scheduled around noon and midnight on the second, third, and fourth days (see schedule) for a total of six slots. The A-frame and small capstan will be needed for this operation. Blake Watkins will direct these operations.

4.3 Gas Array, Sediment Trap Array, and WireWalker recovery

In the morning of December 20th, after the optics cast has been completed, the ship shall transit for the recovery of the Gas Array. The A-frame and the Sea-Mac winch will be needed to retrieve the sediment trap array. After the Gas Array is recovered, the ship shall transit to recover the floating sediment trap array. On completion of sediment trap array recovery, the ship shall transit to recover the Wirewalker. Blake Watkins will be in charge of these operations. After the Wirewalker is recovered, the ship shall transit to Station 52.

4.4 Station 52 - WHOTS-16 Mooring

The anchor position of the WHOTS-16 mooring is 22° 40.01'N 157° 56.96'W. The watch circle of the buoy is about 2 nautical miles. Generally, the buoy stays on the edge of the watch circle. The buoy can be detected via radar in good weather conditions but is harder to detect with larger sea states. Upon arrival at Station 52 on December 20th, one 200 m CTD yo-yo cast (Sect. 5.4.1), a Hyperpro cast, and ADCP intercomparisons will be conducted. Following a Trace Metal CTD cast, the ship will transit to Station Kaena.

4.5. Station Kaena (21° 50.8'N, 158° 21.8'W)

A near-bottom CTD cast (~2500 m) will be conducted at this location in the evening of December 20th. Once the CTD cast is complete, the ship shall return to Pier 35.

4.6. Acoustic Doppler Current Profiler

The ship's acoustic Doppler current profilers (ADCP) will be in operation during the duration of the cruise. The OTG technicians will be in charge of the ADCP system.

4.7. Thermosalinograph, Fluorometer and pCO₂

The ship's thermosalinograph, fluorometer and pCO₂ sampling the uncontaminated seawater supply system will be in operation during the duration of the cruise while the ship is outside of Honolulu Harbor. Salinity samples to calibrate the thermosalinograph will be taken from the intake hose at 4-hour intervals throughout the duration of the cruise by the science personnel. The ship's meteorological system shall be in operation throughout the cruise. Access to real-time underway data through the ship's network will be required. The OTG technicians will be in charge of the thermosalinograph, fluorometer, and meteorological suite operations.

4.7.1. SeaFlow, Inline C-Star Transmissometer and Imaging FlowCytobot (IFCB)

In addition to the continuous thermosalinograph and fluorometer sampling, the SeaFlow, an inline C-Star Transmissometer, and the IFCB will sample continuously from the uncontaminated seawater supply system throughout the duration of the cruise while the ship is outside of Honolulu Harbor. Access to real-time underway data through the ship's network is required. The SCOPE Ops technicians and UH personnel will be in charge of these instruments and operations.

4.8. Trace Metal Clean Rosette

Vertical profiles between 0-600m will be conducted for trace metal analysis using a rosette package with autonomous Auto Fire Module. This mini-CTD rosette consists of a SeaBird CTD attached to a 12-place rosette with 8 liter Niskin sampling bottles. The rosette is approximately 5 ft x 5ft x 4 ft and weighs 355/565 lbs

HOT 325 Cruise Plan – Operational Copy

in air empty/full. We will deploy the CTD rosette using the SeaMac winch, delrin block and 1/4" Amsteel line using trace metal clean procedures from the stern of the vessel using the A-Frame.

4.9. Scripps Plankton Camera Cast

An optical Plankton Camera package called belonging to colleagues at Scripps University will be deployed four times during the cruise, twice in the day and twice at night. This will be deployed using the capstan in identical manner to the HOT/SCOPE Optics package (Sect. 4.2.10), except there will be only one profile instead of three.

5.0 EQUIPMENT

5.1. The HOT science party shall be bringing the following

1. Seabird CTD system, all sensors, deck boxes and computer CTD acquisition systems
2. Rosette and 24 12L Bullister sampling bottles, and all associated spare parts
3. Lowered Acoustic Doppler Current Profiler (LADCP)
4. One 20 ft. laboratory van (#23) with assorted equipment for radioisotope and general use, and one 10x8 ft. equipment van (PO) for equipment and spare storage.
5. Distilled, deionized water and all required chemicals and isotopes
6. Large vacuum waste containers
7. Liquid nitrogen dewars
8. Drifting sediment trap array with strobe lights, satellite and radio transmitters, floats, weights, line, sediment traps and crosses.
9. Drifting primary production array with strobe lights, satellite and radio transmitters, floats, weights, line primary production bottles and spreader bars.
10. Drifting gas array with strobe lights, satellite and radio transmitters, floats, weights, line, 4 L bottles and short mounting bars.
11. Drifting Wirewalker™ array with surface buoy, strobe lights, satellite transmitters, floats, weights, 400m and cable.
12. Drifting IRSC Sediment Trap array with surface buoy, strobe lights, satellite transmitters, floats, weights, line, and instrument cage.
13. Oxygen titration system
14. Plankton nets and towing lines
15. Desktop and laptop personal computers
16. Assorted tools
17. All required sampling bottles
18. Pertinent MSDS
19. Wirewalker™
20. SeaFlow
21. Inline C-Star Transmissometer
22. Imaging FlowCytobot (IFCB)
23. Trace metal clean rosette with 8L Niskin bottles and programmable CTD

5.2. We will need the use of the following ship's equipment:

1. A-frame
2. A-frame block assembly
3. CTD winch
4. Electric power
 - 440/480 VAC, 3 phase 60Hz, 60amp for winches
 - 208 VAC single phase at 60 amps for lab vans

5. Space on upper 01 deck port side for one 10 ft van (**Blue Equipment van**)
6. Space on upper 01 deck port side for one 20 ft van (**#23**)
7. Space on upper 01 deck starboard side for trace metal 20 ft van (**#24**)
8. Space on 02 deck for incubators
9. Space on deck for ~4 deck baskets of array gear
10. Small capstan (~ 10 m/min)
11. SeaMac Winch
12. Radio direction finder
13. Hand-held VHF transceivers
14. Shackles, sheaves, hooks and lines
15. Precision depth recorder
16. Shipboard Acoustic Doppler Current Profiler
17. Thermosalinograph, $p\text{CO}_2$ system, and Fluorometer
18. Meteorological suite
19. Grappling hooks and line
20. Navlink2 PC or equivalent
21. Running fresh water and seawater, hoses
22. Uncontaminated seawater supply
23. Source of compressed air for Trace Metal pump
24. -80°C Freezer
25. 4°C Refrigerator and -20°C Freezer
26. Distilled, deionized water system
27. Electronic mail system
28. GPS system
29. Underway/on-station data acquisition system for meteorological instruments, ADCP, thermosalinograph, fluorometer, SeaFlow, inline C-Star transmissometer and IFCB and access to real-time data through the network.
30. OTG's 24-place rosette, and 24 12-l water sampling bottles (to be used as spare)
31. ~1300 lb weight
32. Remote CTD dbar pressure display in the winch operator area.
33. Monitor in CTD Lab displaying ship coordinates, bottom depth and GMT.
34. OTG's transmissometer (preferably SN 1366)
35. Trace metal free block
36. Amsteel Line (1/4") for trace metal clean work

6.0 Satellite Position Transmitters Summary

Array Name	RockBlock ID	XEOS ID	Argos ID	Radio Frequency
IRSC Traps (IRSC)	03	266 and 81		CH.74 (156.725 MHz)
Sediment Trap (ST)	06	268 and 78		CH.69 (156.475 MHz)
WireWalker (WW)		77 and 80		
Primary Production (PP)	05	267 and 79		CH.73 (156.675 MHz)
Gas Array (GA)	05	267 and 79		CH.73 (156.675 MHz)

NOTE: Array tracking is facilitated through the SOEST Cruise and Drifter Tracks tool found at <http://hahana.soest.hawaii.edu/nowcast/loctable.html>

Ship: R/V *Kilo Moana*

HOT 325 CTD CASTS

Date: Dec 16 – Dec 20, 2020

Cast	Depth	Samples	#Bottles
<u>Kahe Pt.</u>			
s1c1	1000 m	O ₂ , Temp, DIC/Alk, pH, Nuts, LLN, LLP, Chl a, Salts	23
<u>Station ALOHA</u>			
s2c1	1000 m	Primary Production (3@ 5, 25, 45, 75, 100, 125, 150, 2@ 175) Chl a, FCM, Salts	24
s2c2	4740 m (PO-1)	O ₂ , Temp, DOC, DIC/Alk, pH, Ref Si, Nuts, Salts KO (1 @ 5, 500, 1000)	24
s2c3	1000 m (PO-2)	O ₂ , Temp, DOC, DIC/Alk, pH, Nuts, Ref Si, Salts KO (1 @ 300)	24
s2c4	1000 m	PC/PN, SCOPE DNA (1@5,25,45,75), Salts	18
s2c5	1000 m	PPO ₄ , Salts SD (6@20-25(Mixed Layer))	23
s2c6	1000 m (BEACH)	O ₂ , Temp, DIC/Alk, pH, Nuts, LLN, LLP, DOC, Keeling, Quay, Salts	24
s2c7	1000 m	SCOPE DNA(1@ 100,125,150,175, Salts	22
s2c8	1000 m	Gas Array(3@5,25,45,75,100,125), Salts	22
s2c9	1000 m	SCOPE DNA(1@200,225,250,275), MC (1@5, 25, 45, 75, 100, 125, 150, 175), Salts	18
s2c10	1000 m	PSi, Salts	24
s2c11	1000 m	RL (1 @ 5, 25, 45, 75, 100, 125, 150, 175), Salts	17
s2c12	1000 m	ATP, SCOPE DNA(1@300,400,500,770), Salts	23
s2c13	1000 m	HOT PO (6@1020), Salts	10
s2c14	1000 m	HPLC, Chl a, Salts, ES (1@ DCM, pb 1@ 25)	14
s2c15	4740 m (PO-3)	Oxygen, SCOPE DNA(1@ 1000,2000,3000,4000), Salts	12
<u>WHOTS Mooring</u>			
s52c1	200 m yo-yo	DIC/TA(1@5)	1
<u>Kaena</u>			
s6c1	2400 m	Chl a, Salts	13

MC=Matt Church, **KO**=Keri Opalk, **SD** = Sonya Dyhrman, **RL**=Robert Letscher, **ES** = Eric Shimabukuro

Ship: R/V Kilo Moana**HOT 325****Date: Dec 17 – Dec 21, 2020**

TIME	Thur. 12/17	Fri. 12/18	Sat. 12/19	Sun. 12/20	Mon. 12/21
0000		Deploy Sed Traps	Transit to pump tanks Incinerator		
0100		Deploy WireWalker			
0200		S2C1 PP	S2C8 Gas Array		
0300				Optics	
0400		Deploy PP Array	Deploy Gas Array		
0500		S2C2 PO-1(Deep)	S2C9 Open	Transit Gas Array	
0600				Recover Gas Array Transit Sed Traps	
0700	All Sci. Aboard		Trace Metal Cast 3	Recover Sed Traps	
0800	Depart Pier 35		S2C10 PSi	Transit WireWalker Recover WireWalker	Arrive Pier 35
0900		Trace Metal Cast 2		Transit IRSC Traps Recover IRSC Traps	
1000	Arrive Kahe(10:30) Weight Cast	Plankton Camera Cast		Pump Tanks/ Transit Station 52	
1100	Hyperpro	S2C3 PO-2 (Begin 36 hr)	S2C11 Open		
1200	S1C1 Kahe	Net Tow	Net Tow Net Tow	HyperPro	
1300	Trace Metal Cast 1	HyperPro		S52C1 WHOTS	
1400	Transit to ALOHA	S2C4 PC/PN	S2C12 ATP	ADCP Inter-comp	
1500		Transit to pump tanks	Plankton Camera Cast	Trace Metal Cast 4	
1600		S2C5 PPO4			
1700		Transit to PP array	S2C13 Open	Transit to Kaena Incinerator	
1800		Recover PP array	Transit to pump tanks Incinerator		
1900					
2000		S2C6 BEACH	S2C14 HPLC		
2100		Plankton Camera Cast	Plankton Camera Cast		
2200	Arrive ALOHA	Net Tow Net Tow	Net Tow	S6C1 Kaena	
2300	Deploy IRSC Traps	S2C7 Open	S2C15 PO-3 (Deep) (end 36 hours)		

December 18th: Sunrise 0703, Sunset 1754

6.0 HOT-325 Watch Schedule

0300-1500

Dan Fitzgerald – Tag

Fernando Pacheco – Console, Watch Leader

Dan Sadler –Water Boss, Alt Tag

Ryan Tabata –Tag

1500-0300

Brandon Brenes – Water Boss, Alt Tag

Lucie Knor – Console

Tully Rohrer – Chief Scientist, Watch Leader

Eric Shimabukuro – Tag

Andrés Salazar Estrada – Tag

At Large

Eleanor Bates

Tim Burrell

Nick Hawco

Blake Watkins

OTG

Trevor Young (lead)

Lance Frymire